

Liftcrane Boom Capacities


Boom No. B10:290

33 120 kg Crane Counterweight

10 500 kg Carbody Counterweight

360 Degree Rating

MLC100A-1 SERIES 2

 **LIFTING CAPACITIES:** Lifting capacities for various boom lengths and operating radii are for freely suspended loads and may be based on percent of static tipping or strength of structural components. Capacities must be reduced by applicable deducts.

Upper boom point capacity for liftcrane service with single part whip line from Drum 3 is 9 070 kg. When Drum 1 or Drum 2 is used, capacity with single part whip line is 12 520 kg. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom point sheaves, is considered part of load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

BOOM BACKWARD STABILITY: A minimum of 2 parts hoist line is required when using Drum 2 or 3 on 16,0 m boom length to maintain boom stability at high boom angles. **Caution: Do not operate using Drum 2 or 3 without required parts of hoist line.** Boom may not lower and boom hoist wire rope may go slack causing wire rope damage or failure.

OPERATING CONDITIONS: Machine to operate on a firm, level, and uniformly supporting surface. Refer to Boom Rigging **No. 80121889**, Wire Rope Specifications chart **No. 9800-A**, Counterweight Arrangements chart **No. 9794-A**, and Wind Conditions chart **No. 9799-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.


MACHINE TRAVEL: Machine to travel on a firm, level, and uniformly supporting surface. Boom must be within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specifications chart **No. 9798-A**.



OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block.



BOOM ANGLE: Boom angle in degrees (°) is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.



BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 6 480 mm crawlers, 900 mm treads, 4 390 mm gantry, 8 part boom hoist reeving, two 32 mm boom pendants, 33 120 kg crane counterweight, and 10 500 kg carbody counterweight.

Consult chart **No. 9801-AM** when Jib No. 117 is attached.

Upper Boom Point Deduct

Deduct 260 kg from capacities when upper boom point is attached. Deduct does not apply to 16,0 m thru 19,0 m boom lengths.

Third Line Deduct

Deduct 120 kg from capacities when boom top is equipped with optional 3rd sheave wire rope guide.

Deduct From Capacities When Jib No. 117 Is Attached

Jib Length (m)	Deduct (kg)
9,1	2 050
12,2	2 400
15,2	2 800
18,3	3 350

Weight of jib and 325 kg suspended beneath jib point have been included in determination of deduct.

Refer to Table 1 for raising ability with the maximum weight of all load blocks, hooks, weight ball, slings, and hoist lines beneath boom point sheaves. For block weights shown with #, load blocks, hooks, weight ball, and slings must remain on ground until combined weights are within rated capacity of chart. Raising is not permitted in shaded areas of table.


Combined weight beneath boom point sheaves must not exceed block weight shown.

Table 1


Boom Length (m)	Over End or Side of Crawlers
	Block Weight (kg)
16,0 - 49,0	1 725
52,0	1 200
55,0 - 61,0	325

REFERENCE ONLY!

Explanation of Symbols




Boom No. B10:290



Crane Counterweight
+
Carbody Counterweight



360 Degree Rating



Boom Length



Operating Radius
(see page 1)



Boom Angle
(see page 1)





Boom Point Elevation
(see page 1)



Lifting Capacities
(see page 1)

MLC100A-1 S-2

ASME B30.5



33 120 kg
+
10 500 kg



16,0 m

m	°	m	kg
4,0	80,6	17,9	88 300
4,5	78,7	17,8	81 200
5,0	76,8	17,6	73 400
5,5	75,0	17,5	67 000
6,0	73,1	17,4	61 600
6,5	71,2	17,2	55 200
7,0	69,3	17,0	49 400
7,5	67,4	16,8	44 400
8,0	65,4	16,6	40 300
8,5	63,4	16,3	36 900
9,0	61,4	16,0	34 000
9,5	59,3	15,8	31 500
10,0	57,2	15,4	29 300
10,5	55,0	15,1	27 400
11,0	52,7	14,7	25 700
11,5	50,4	14,3	24 200
12,0	48,0	13,9	22 800
13,0	42,9	12,8	20 500
14,0	37,3	11,6	18 600
15,0	30,7	10,1	16 900

19,0 m

m	°	m	kg
4,6	80,3	20,8	79 300
5,0	78,9	20,7	73 300
5,5	77,4	20,6	66 800
6,0	75,8	20,5	61 500
6,5	74,3	20,3	55 200
7,0	72,7	20,2	49 400
7,5	71,1	20,0	44 400
8,0	69,5	19,8	40 300
8,5	67,9	19,6	36 800
9,0	66,2	19,4	34 000
9,5	64,5	19,2	31 500
10,0	62,8	18,9	29 300
10,5	61,1	18,6	27 400
11,0	59,4	18,3	25 700
11,5	57,6	18,0	24 200
12,0	55,8	17,7	22 800
13,0	52,0	16,9	20 500
14,0	48,0	16,1	18 500
15,0	43,8	15,1	16 900
16,0	39,1	13,9	15 500
17,0	34,0	12,5	14 300
18,0	28,0	10,8	13 200

22,0 m

m	°	m	kg
4,9	80,8	23,8	72 100
5,0	80,5	23,8	71 600
5,5	79,1	23,7	66 900
6,0	77,8	23,6	61 500
6,5	76,5	23,5	55 400
7,0	75,1	23,3	49 500
7,5	73,8	23,2	44 500
8,0	72,4	23,0	40 400
8,5	71,0	22,9	37 000
9,0	69,6	22,7	34 100
9,5	68,2	22,5	31 600
10,0	66,8	22,3	29 500
10,5	65,4	22,0	27 500
11,0	64,0	21,8	25 800
11,5	62,5	21,5	24 300
12,0	61,0	21,3	23 000
13,0	58,0	20,6	20 600
14,0	54,8	20,0	18 700
15,0	51,5	19,2	17 000
16,0	48,1	18,3	15 700
17,0	44,4	17,4	14 400
18,0	40,5	16,2	13 400
19,0	36,3	15,0	12 500
20,0	31,6	13,4	11 600
21,0	26,0	11,6	10 900






MLC100A-1 S-2






ASME B30.5








 33 120 kg
+
10 500 kg





 25,0 m			
 m	 °	 m	 kg
5,5	80,5	26,7	64 700
6,0	79,3	26,6	61 400
6,5	78,1	26,5	55 300
7,0	76,9	26,4	49 500
7,5	75,8	26,3	44 500
8,0	74,6	26,1	40 400
8,5	73,4	26,0	36 900
9,0	72,2	25,8	34 100
9,5	71,0	25,7	31 600
10,0	69,7	25,5	29 400
10,5	68,5	25,3	27 500
11,0	67,3	25,1	25 700
11,5	66,0	24,9	24 200
12,0	64,7	24,6	22 900
13,0	62,2	24,1	20 500
14,0	59,5	23,5	18 600
15,0	56,8	22,9	17 000
16,0	54,0	22,2	15 600
17,0	51,1	21,4	14 400
18,0	48,1	20,6	13 300
19,0	44,9	19,6	12 400
20,0	41,5	18,5	11 500
21,0	37,9	17,3	10 800
22,0	33,9	15,9	10 100
23,0	29,5	14,2	9 500
24,0	24,3	12,2	9 000

 28,0 m			
 m	 °	 m	 kg
5,8	80,9	29,7	58 600
6,0	80,5	29,7	57 900
6,5	79,4	29,6	54 300
7,0	78,4	29,5	49 500
7,5	77,3	29,4	44 500
8,0	76,3	29,3	40 300
8,5	75,2	29,1	36 900
9,0	74,2	29,0	34 100
9,5	73,1	28,8	31 600
10,0	72,0	28,7	29 400
10,5	70,9	28,5	27 400
11,0	69,8	28,3	25 700
11,5	68,7	28,1	24 200
12,0	67,6	27,9	22 900
13,0	65,4	27,5	20 500
14,0	63,1	27,0	18 600
15,0	60,8	26,5	16 900
16,0	58,4	25,9	15 600
17,0	56,0	25,2	14 300
18,0	53,4	24,5	13 300
19,0	50,8	23,7	12 400
20,0	48,1	22,8	11 500
21,0	45,3	21,9	10 800
22,0	42,3	20,8	10 100
23,0	39,1	19,6	9 500
24,0	35,7	18,3	9 000
25,0	32,0	16,8	8 500
26,0	27,9	15,0	8 000
27,0	23,0	12,8	7 600

 31,0 m			
 m	 °	 m	 kg
6,7	80,1	32,6	51 900
7,0	79,5	32,6	49 100
7,5	78,6	32,5	44 400
8,0	77,6	32,3	40 300
8,5	76,7	32,2	36 900
9,0	75,7	32,1	34 000
9,5	74,8	32,0	31 500
10,0	73,8	31,8	29 300
10,5	72,8	31,7	27 400
11,0	71,9	31,5	25 600
11,5	70,9	31,3	24 100
12,0	69,9	31,1	22 800
13,0	67,9	30,8	20 400
14,0	65,9	30,3	18 500
15,0	63,8	29,8	16 900
16,0	61,8	29,3	15 500
17,0	59,6	28,7	14 300
18,0	57,5	28,1	13 200
19,0	55,2	27,4	12 300
20,0	52,9	26,7	11 400
21,0	50,6	25,9	10 700
22,0	48,1	25,0	10 000
23,0	45,6	24,1	9 400
24,0	42,9	23,0	8 900
25,0	40,1	21,9	8 400
26,0	37,1	20,6	7 900
27,0	33,8	19,2	7 500
28,0	30,3	17,6	7 100

MLC100A-1 S-2

ASME B30.5



33 120 kg
+
10 500 kg



360°

34,0 m			
m	°	m	kg
6,7	80,9	35,7	48 000
7,0	80,4	35,6	47 000
7,5	79,6	35,5	44 400
8,0	78,7	35,4	40 200
8,5	77,9	35,3	36 800
9,0	77,0	35,2	33 900
9,5	76,1	35,1	31 400
10,0	75,3	34,9	29 200
10,5	74,4	34,8	27 300
11,0	73,5	34,6	25 600
11,5	72,6	34,5	24 100
12,0	71,7	34,3	22 700
13,0	69,9	34,0	20 400
14,0	68,1	33,6	18 400
15,0	66,3	33,1	16 800
16,0	64,4	32,7	15 400
17,0	62,5	32,2	14 200
18,0	60,6	31,6	13 100
19,0	58,7	31,0	12 200
20,0	56,7	30,4	11 300
21,0	54,6	29,7	10 600
22,0	52,5	28,9	9 900
23,0	50,3	28,1	9 300
24,0	48,1	27,3	8 800
25,0	45,8	26,3	8 300
26,0	43,3	25,3	7 800
27,0	40,8	24,2	7 400
28,0	38,1	22,9	7 000
29,0	35,3	21,6	6 700
30,0	32,2	20,0	6 300
32,0	25,1	16,3	5 700

37,0 m			
m	°	m	kg
7,3	80,7	38,6	43 600
7,5	80,4	38,6	42 700
8,0	79,7	38,5	40 200
8,5	78,9	38,4	36 700
9,0	78,1	38,3	33 900
9,5	77,3	38,2	31 400
10,0	76,5	38,0	29 200
10,5	75,7	37,9	27 200
11,0	74,9	37,8	25 500
11,5	74,1	37,6	24 000
12,0	73,3	37,5	22 600
13,0	71,6	37,2	20 300
14,0	70,0	36,8	18 300
15,0	68,3	36,4	16 700
16,0	66,7	36,0	15 300
17,0	65,0	35,5	14 100
18,0	63,2	35,0	13 000
19,0	61,5	34,5	12 100
20,0	59,7	33,9	11 200
21,0	57,9	33,3	10 500
22,0	56,0	32,7	9 800
23,0	54,1	32,0	9 200
24,0	52,2	31,2	8 700
25,0	50,2	30,4	8 200
26,0	48,1	29,5	7 700
27,0	46,0	28,6	7 300
28,0	43,8	27,6	6 900
29,0	41,5	26,5	6 600
30,0	39,1	25,3	6 200
32,0	33,8	22,5	5 600
34,0	27,7	19,1	5 100


40,0 m			
m	°	m	kg
7,9	80,6	41,5	39 600
8,0	80,4	41,5	39 200
8,5	79,7	41,4	36 600
9,0	79,0	41,3	33 800
9,5	78,2	41,2	31 300
10,0	77,5	41,1	29 100
10,5	76,8	41,0	27 100
11,0	76,0	40,9	25 400
11,5	75,3	40,7	23 900
12,0	74,6	40,6	22 600
13,0	73,1	40,3	20 200
14,0	71,6	40,0	18 300
15,0	70,0	39,6	16 600
16,0	68,5	39,2	15 300
17,0	66,9	38,8	14 000
18,0	65,4	38,4	13 000
19,0	63,8	37,9	12 000
20,0	62,2	37,4	11 200
21,0	60,5	36,8	10 400
22,0	58,9	36,2	9 800
23,0	57,2	35,6	9 200
24,0	55,4	34,9	8 600
25,0	53,7	34,2	8 100
26,0	51,9	33,4	7 700
27,0	50,0	32,6	7 200
28,0	48,1	31,7	6 900
29,0	46,1	30,8	6 500
30,0	44,1	29,8	6 200
32,0	39,8	27,5	5 600
34,0	35,0	24,9	5 000
36,0	29,6	21,7	4 600
38,0	23,1	17,6	4 200

MLC100A-1 S-2

ASME B30.5



B10



33 120 kg
+
10 500 kg



360°


43,0 m			
m	°	m	kg
8,5	80,4	44,5	35 300
9,0	79,8	44,4	33 500
9,5	79,1	44,3	31 200
10,0	78,4	44,2	29 000
10,5	77,7	44,1	27 100
11,0	77,0	44,0	25 300
11,5	76,4	43,9	23 800
12,0	75,7	43,7	22 500
13,0	74,3	43,5	20 100
14,0	72,9	43,2	18 200
15,0	71,5	42,8	16 500
16,0	70,1	42,5	15 200
17,0	68,7	42,1	13 900
18,0	67,2	41,7	12 900
19,0	65,8	41,2	11 900
20,0	64,3	40,8	11 100
21,0	62,8	40,3	10 300
22,0	61,3	39,7	9 700
23,0	59,7	39,1	9 100
24,0	58,2	38,5	8 500
25,0	56,6	37,9	8 000
26,0	55,0	37,2	7 600
27,0	53,3	36,5	7 100
28,0	51,6	35,7	6 800
29,0	49,9	34,9	6 400
30,0	48,1	34,0	6 100
32,0	44,4	32,1	5 500
34,0	40,5	29,8	4 900
36,0	36,1	27,3	4 500
38,0	31,3	24,3	4 000
40,0	25,6	20,5	3 700

46,0 m			
m	°	m	kg
9,1	80,3	47,4	32 000
9,5	79,8	47,3	30 800
10,0	79,2	47,2	28 900
10,5	78,5	47,1	27 000
11,0	77,9	47,0	25 300
11,5	77,3	46,9	23 700
12,0	76,6	46,8	22 400
13,0	75,3	46,6	20 000
14,0	74,0	46,3	18 100
15,0	72,7	46,0	16 400
16,0	71,4	45,6	15 100
17,0	70,1	45,3	13 800
18,0	68,8	44,9	12 800
19,0	67,4	44,5	11 800
20,0	66,1	44,1	11 000
21,0	64,7	43,6	10 300
22,0	63,3	43,1	9 600
23,0	61,9	42,6	9 000
24,0	60,5	42,0	8 400
25,0	59,0	41,4	7 900
26,0	57,6	40,8	7 500
27,0	56,1	40,1	7 000
28,0	54,5	39,4	6 700
29,0	53,0	38,7	6 300
30,0	51,4	37,9	6 000
32,0	48,1	36,2	5 400
34,0	44,7	34,3	4 800
36,0	41,0	32,1	4 400
38,0	37,0	29,6	4 000
40,0	32,6	26,7	3 600
42,0	27,6	23,2	3 300
44,0	21,5	18,8	2 900

49,0 m			
m	°	m	kg
9,1	80,9	50,5	28 500
9,5	80,4	50,4	28 200
10,0	79,8	50,3	27 800
10,5	79,2	50,2	26 900
11,0	78,7	50,1	25 200
11,5	78,1	50,0	23 700
12,0	77,5	49,9	22 300
13,0	76,3	49,7	19 900
14,0	75,0	49,4	18 000
15,0	73,8	49,1	16 300
16,0	72,6	48,8	15 000
17,0	71,4	48,5	13 700
18,0	70,1	48,1	12 700
19,0	68,9	47,8	11 700
20,0	67,6	47,3	10 900
21,0	66,4	46,9	10 100
22,0	65,1	46,5	9 500
23,0	63,8	46,0	8 900
24,0	62,5	45,5	8 300
25,0	61,1	44,9	7 800
26,0	59,8	44,3	7 400
27,0	58,4	43,7	6 900
28,0	57,0	43,1	6 600
29,0	55,6	42,4	6 200
30,0	54,2	41,7	5 900
32,0	51,2	40,2	5 200
34,0	48,1	38,5	4 700
36,0	44,9	36,6	4 300
38,0	41,5	34,4	3 800
40,0	37,8	32,0	3 500
42,0	33,8	29,2	3 100
44,0	29,3	25,9	2 800
46,0	24,0	21,8	2 500

MLC100A-1 S-2

ASME B30.5



33 120 kg
+
10 500 kg



52,0 m			
m	°	m	kg
9,8	80,7	53,4	24 100
10,0	80,4	53,4	23 900
10,5	79,9	53,3	23 700
11,0	79,3	53,2	23 400
11,5	78,7	53,1	23 100
12,0	78,2	53,0	22 100
13,0	77,1	52,7	19 900
14,0	75,9	52,5	17 900
15,0	74,8	52,2	16 300
16,0	73,6	51,9	14 900
17,0	72,5	51,6	13 600
18,0	71,3	51,3	12 600
19,0	70,2	50,9	11 600
20,0	69,0	50,6	10 800
21,0	67,8	50,2	10 100
22,0	66,6	49,7	9 400
23,0	65,4	49,3	8 800
24,0	64,2	48,8	8 200
25,0	62,9	48,3	7 700
26,0	61,7	47,8	7 300
27,0	60,4	47,2	6 900
28,0	59,1	46,6	6 500
29,0	57,8	46,0	6 100
30,0	56,5	45,4	5 800
32,0	53,8	44,0	5 200
34,0	51,0	42,4	4 600
36,0	48,1	40,7	4 200
38,0	45,1	38,8	3 800
40,0	41,9	36,7	3 400
42,0	38,4	34,3	3 100
44,0	34,7	31,5	2 800
46,0	30,6	28,4	2 500
48,0	25,9	24,6	2 200

55,0 m			
m	°	m	kg
10,4	80,6	56,3	20 800
10,5	80,4	56,3	20 800
11,0	79,9	56,2	20 500
11,5	79,4	56,1	20 300
12,0	78,8	56,0	20 100
13,0	77,8	55,8	19 400
14,0	76,7	55,6	17 800
15,0	75,6	55,3	16 200
16,0	74,5	55,1	14 800
17,0	73,5	54,8	13 500
18,0	72,4	54,4	12 500
19,0	71,3	54,1	11 500
20,0	70,2	53,8	10 700
21,0	69,1	53,4	10 000
22,0	67,9	53,0	9 300
23,0	66,8	52,6	8 700
24,0	65,7	52,1	8 100
25,0	64,5	51,6	7 600
26,0	63,3	51,2	7 200
27,0	62,2	50,6	6 700
28,0	61,0	50,1	6 400
29,0	59,8	49,5	6 000
30,0	58,6	48,9	5 700
32,0	56,1	47,6	5 100
34,0	53,5	46,2	4 500
36,0	50,9	44,6	4 100
38,0	48,1	42,9	3 700
40,0	45,3	41,0	3 300
42,0	42,2	38,9	3 000
44,0	39,0	36,5	2 700
46,0	35,5	33,9	2 400
48,0	31,8	30,9	2 100
50,0	27,5	27,3	1 900


58,0 m			
m	°	m	kg
11,0	80,5	59,3	19 700
11,5	79,9	59,2	19 500
12,0	79,4	59,1	19 300
13,0	78,4	58,9	18 900
14,0	77,4	58,7	17 700
15,0	76,4	58,4	16 000
16,0	75,4	58,2	14 700
17,0	74,3	57,9	13 400
18,0	73,3	57,6	12 400
19,0	72,3	57,3	11 400
20,0	71,2	57,0	10 600
21,0	70,2	56,6	9 800
22,0	69,1	56,2	9 200
23,0	68,1	55,8	8 600
24,0	67,0	55,4	8 000
25,0	65,9	55,0	7 500
26,0	64,8	54,5	7 000
27,0	63,7	54,0	6 600
28,0	62,6	53,5	6 200
29,0	61,5	53,0	5 900
30,0	60,4	52,4	5 500
32,0	58,1	51,2	4 900
34,0	55,7	49,9	4 400
36,0	53,3	48,5	3 900
38,0	50,8	46,9	3 500
40,0	48,1	45,2	3 200
42,0	45,4	43,3	2 800
44,0	42,6	41,2	2 500
46,0	39,5	38,9	2 200
48,0	36,3	36,3	2 000
50,0	32,8	33,4	1 800

MLC100A-1 S-2

ASME B30.5



B10



33 120 kg
+
10 500 kg



360°

 m	 °	 m	 kg
11,0	80,9	62,3	17 600
11,5	80,4	62,2	17 400
12,0	79,9	62,1	17 200
13,0	79,0	61,9	16 900
14,0	78,0	61,7	16 500
15,0	77,1	61,5	15 800
16,0	76,1	61,3	14 600
17,0	75,1	61,0	13 300
18,0	74,2	60,7	12 200
19,0	73,2	60,4	11 300
20,0	72,2	60,1	10 500
21,0	71,2	59,8	9 700
22,0	70,2	59,4	9 000
23,0	69,2	59,1	8 400
24,0	68,2	58,7	7 900
25,0	67,2	58,2	7 400
26,0	66,2	57,8	6 900
27,0	65,1	57,3	6 500
28,0	64,1	56,9	6 100
29,0	63,0	56,4	5 700
30,0	62,0	55,8	5 400
32,0	59,8	54,7	4 800
34,0	57,6	53,5	4 300
36,0	55,3	52,2	3 800
38,0	53,0	50,7	3 400
40,0	50,6	49,1	3 000
42,0	48,1	47,4	2 700
44,0	45,6	45,5	2 400
46,0	42,8	43,4	2 100
48,0	40,0	41,1	1 900

PREFERENCE ONLY!