

Wire Rope Specifications

MLC300 VPC-MAX

Liftcrane - Boom No. B85:505-500
with Mast No. M11:503 and
7,0 m (23.0 ft) Extended Upper Boom Point

Wire Rope Lengths - Single Hoist Drum									
Boom Length		Whip Line Drum 2 or 3 or 6		Hoist Line Drum 1		Total Parts of Line	Hoist Line Drum 2		Total Parts of Line
		1 Part		Meters	Feet		Meters	Feet	
Meters	Feet	Meters	Feet	Meters	Feet		Meters	Feet	
83,0	272.3	190	630	635	2,080	6	465	1,510	4
86,0	282.2	200	650	660	2,150	6	385	1,250	3
89,0	292.0	205	670	680	2,220	6	395	1,290	3
92,0	301.8	210	690	695	2,280	6	410	1,330	3
95,0	311.7	215	710	720	2,350	6	420	1,370	3
98,0	321.5	220	730	635	2,080	5	430	1,410	3
101,0	331.4	230	750	655	2,140	5	445	1,450	3
104,0	341.2	235	770	670	2,190	5	455	1,490	3
107,0	351.0	240	790	690	2,250	5	355	1,150	2
110,0	360.9	245	800	590	1,930	4	360	1,180	2
113,0	370.7	250	820	605	1,980	4	370	1,210	2
116,0	380.6	260	840	620	2,030	4	380	1,240	2
119,0	390.4	265	860	635	2,080	4	390	1,270	2
122,0	400.3	270	880	650	2,130	4	400	1,300	2
125,0	410.1	275	900	535	1,740	3	410	1,330	2
128,0	419.9	285	920	545	1,780	3	415	1,360	2
131,0	429.8	290	940	555	1,820	3	425	1,390	2

Note: Above hoist line lengths are based on single part lead line. Hoist and whip line lengths will allow hook to touch ground. When block travel below ground is required, add additional rope equal to parts of line times added travel distance. Hoisting distance or line pull may be limited when block travel below ground is required.

Hoist Reeving for Main Load Block - Single Lead Line (Drum 1 or 2)						
No. Parts of Line	1	2	3	4	5	6
Maximum Load - kg	16 670	33 340	50 010	66 680	83 350	100 000
Maximum Load - lb	36,760	73,520	110,280	147,040	183,800	220,500
Maximum Load per Part of Line - kg	16 670	16 670	16 670	16 670	16 670	16 666
Maximum Load per Part of Line - lb	36,760	36,760	36,760	36,760	36,760	36,750

Wire Rope Specifications

Liftcrane - Boom No. B85:505-500
with Mast No. M11:503 and
7,0 m (23.0 ft) Extended Upper Boom Point

Hoist Reeving for Whip Load Block - Single Lead Line (Drum 6)	
No. Parts of Line	1
Maximum Load - kg	13 600
Maximum Load - lb	30,000
Maximum Load per Part of Line - kg	13 600
Maximum Load per Part of Line - lb	30,000

Hoist Reeving for Whip Load Block - Single Lead Line (Drum 2 or 3)	
No. Parts of Line	1
Maximum Load - kg	16 600
Maximum Load - lb	36,700
Maximum Load per Part of Line - kg	16 670
Maximum Load per Part of Line - lb	36,760

REFERENCE ONLY!

Wire Rope Specifications

Liftcrane - Boom No. B85:505-500
 with Mast No. M11:503 and
 7,0 m (23.0 ft) Extended Upper Boom Point

Wire Rope Specifications	
<u>Rotation Resistant Wire Rope</u>	
Hoist Line:	
28 mm (Drum 1 or 2):	
Wire Rope with Spelter Button and Pad Eye	
Right Hand Lang Lay	
Minimum Breaking Strength = 83 370 kg (183,800 lb)	
Approx. Weight = 4,2 kg/m (2.8 lb/ft)	
No Load Dia. = 28.83 mm (1.135 in) to 29.08 mm (1.145 in)	
MCC Reference No. 81025289, 81026075, or 81024556	
Whip/Auxiliary Line:	
28 mm (Drums 2, 3 or 6):	
Wire Rope with Spelter Button and Pad Eye	
Right Hand Lang Lay	
Minimum Breaking Strength = 83 370 kg (183,800 lb)	
Approx. Weight = 4,2 kg/m (2.8 lb/ft)	
No Load Dia. = 28.83 mm (1.135 in) to 29.08 mm (1.145 in)	
MCC Reference No. 81025289, 81026075, or 81024556	

Maximum Spooling Capacities	
Drum 1: (Hoist Line)	28 mm Wire Rope - 8 Layers - 939 m (3,082 ft)
Drum 2: (Auxiliary Line)	28 mm Wire Rope - 6 Layers - 418 m (1,372 ft)
Drum 3: (Auxiliary Line)	28 mm Wire Rope - 6 Layers - 418 m (1,372 ft)
Drum 6: (Auxiliary Line)	28 mm Wire Rope - 7 Layers - 400 m (1,312 ft)
7 m (22 ft) is deducted from maximum spooling capacity for 3 dead wraps per drum.	

Refer to Drum and Lagging chart **No. 9339-A** and Load Block Reeving in the Operator Manual.

Refer to Block Overhaul Weights chart **No. 9413-A** for minimum weight required for block lowering.

Warning: Free fall operation is limited to 8 300 kg (18,300 lb) per part of line when lowering load with free fall clutch/brake pedal. Hydraulic power shall be used for full line pull. *Permanent brake damage could occur allowing the load to lower uncontrolled.*