



Maximum Allowable Travel Specifications

999 SERIES 2, 3

Boom No. 82
Luffing Jib No. 149

Jobsite Travel

999 SERIES 2 must be equipped with 184,600 Lb. (83 730 kg) crane counterweight and 44,000 Lb. (19 960 kg) carbody counterweight; 999 SERIES 3 must be equipped with 219,600 Lb. (99 610 kg) crane counterweight and 80,000 Lb. (36 290 kg) carbody counterweight. Refer to Operator's Manual for maximum wind speed for various boom and luffing jib lengths. Refer to luffing jib raising procedure for maximum boom and luffing jib lengths lifted unassisted.

1. Machine Travel With Load

- A. Machine can swing and travel with 360 degree rating.
- B. Grade in any direction must not exceed 1/2 in. in 10 Ft. (13mm in 3m).
- C. Travel surface must be firm, level and uniformly supporting. Capacity charts are based on static conditions; therefore judgment must be used to allow for dynamic effects of traveling with load. Carry load as close to ground as possible. Stabilize load with taglines. Travel slowly and smoothly to avoid shock loading boom, luffing jib and rigging.

2. Machine Travel Without Load

- A. **999 SERIES 2** - Position boom to **83 degree boom angle** (plus or minus 1 degree) and position **luffing jib at 40 to 50 degrees** above horizontal. Grade in direction of travel should not exceed **6 percent** (3.4 degrees); **999 SERIES 3** - Position boom to **80 degree boom angle** (plus or minus 1 degree) and set **luffing jib at 40 to 50 degrees** above horizontal. Grade in direction of travel should not exceed **9 percent** (5.1 degrees).
- B. Load blocks and/or hook and weight balls may be suspended beneath boom and luffing jib points, or tied off to machine. Total suspended weight beneath boom point must not exceed 7,500 lb (3 400 kg). Total suspended weight beneath luffing jib point must not exceed 4,000 lb (1 810 kg).
- C. Machine to travel on a firm and uniformly supporting surface. Travel allowed with 360 degree swing up to 1 percent grade; crane upperworks must be in-line with crawlers and grade when grade exceeds 1 percent. Side-to-side grade must not exceed 1 percent (0.5 degrees) measured at boom hinge pins.
- D. Refer to table below for grade vs. angle and boom angle setting. When traveling on **uphill grade, lower boom** the corresponding degrees for grade to be traveled. When traveling on **downhill grade, raise boom** the corresponding degrees for grade to be traveled.
- E. Do not exceed 1 percent (0.5 degrees) side-to-side grade at boom hinge pins when cutting (turning on grade).

Percent Grade Vs. Angle In Degrees and Boom Angle Setting					
Percent Grade	Angle	SERIES 2		SERIES 3	
		Uphill Boom Angle	Downhill Boom Angle	Uphill Boom Angle	Downhill Boom Angle
1	0.5°	82.5°	83.5°	79.5°	80.5°
3	1.7°	81.3°	84.7°	78.3°	81.7°
6	3.4°	79.6°	86.4°	76.6°	83.4°
9	5.1°	Not Allowed	Not Allowed	74.9°	85.1°