


Quick Reference Catalogue

Tower parts





Summary


POTAIN AT A GLANCE	5
HISTORY	7
MANITOWOC DIRECT	8
WHY CHOOSE THE GENUINE PART?	10
CONSUMABLES	13
GREASES FOR MAINTENANCE.....	15
OILS FOR MAINTENANCE	16
HYDRAULICS OIL FOR MAINTENANCE.....	17
PAINTS FOR MAINTENANCE	18
OUR GREASE GUNS.....	20
AUTOMATIC GREASE CARTRIDGES	21
MOTORIZED LUBRICATION	23
ATD GREASE FOR FISH JOINTS	24
LUBRICANT FOR STEEL ROPES.....	26
LUBRICANTS ANALYSIS KITS	27
UNIVERSAL GREASING KIT	29
MISCELLANEOUS CONSUMABLES.....	30
SAFETY	32
ANTICOLLISION: WHY EQUIP YOUR CRANES ?	34
ANTICOLLISION SYSTEM TT3	35
ANTICOLLISION SYSTEM MC602	36
ANTICOLLISION SYSTEM MC603	37
SUPERVISOR FOR ANTI-COLLISION SYSTEMS	38
HOISTING AND TROLLEY WIRE ROPE	39
HYDRAULIC TENSIONER	40
AIRCRAFT WARNING PACKAGE	41
SLEWING RING BOLTS	42
SLEWING RING SEAL KIT.....	43
STRUCTURE	44
UPGRADE CHASSIS	46
SUPPORT PLATES	47



SCREW JACKS PROTECTION	48
DOUBLE ROPE PULLING GRIP WITH SWIVEL	50
K MAST FIXING ANGLE SETS	51
L MAST FIXING ANGLES SETS	52
TIRAX 80	53
1.2M K MASTS	53
MAST PIN SECURING DEVICE	55
PERIPHERICAL PRODUCTS	56
VISION CABINS POTAIN*	57
RETROFIT KIT FOR CAB VISOR	58
CAB HEATING	59
DIALOG WIND ANEMOMETER	60
GIANT DISPLAY XXL	62
JOB SITE LIGHTING FOR GME	63
ADVERTISING LIGHTING	64
DRIVING CAMERA	65
CAB 'IN	66
CCS TOOL KIT	67
JIB LIFTING BEAM	69
MAST PINS SECURING DEVICES	70
REMOTE CONTROLS	72
REMOTE CONTROL ACCESSORIES	73
WALKIE-TALKIES	74
NEW BATTERY 2.75 AH	74
SERVICES	76
DOCUMENT REISSUE	78
GOODIES	79
POTAIN CONNECT+	80
POTAIN GOLD OFFER	82
« STANDARD REPAIR » MOTORS	83
TRAINING ACADEMY POTAIN	84



POTAIN AT A GLANCE





History

Founded in 1928 by Faustin Potain, POTAIN is the world leader in the production of tower cranes and self-erecting cranes (over 60 types of tower crane).

Potain tower cranes, known worldwide for their hoisting capacities, reliability, and innovative designs, are divided into two product lines.

> Self-erecting cranes

Agile and easy to handle, self-erecting cranes are especially suitable for residential construction sites.

The Potain offer in self-erecting cranes, the largest and most innovative on the market, provides the user with the best performance for transport, accessibility, erection, dismantling and maintenance. The offer includes ranges renowned throughout the world: Igo, Igo M, Igo T, Hup and Hup M.

> Top-slewing cranes

Top-slewing cranes are the large construction sites most strategic equipment for productivity. Whether on large infrastructure, high rise jobsites, crowded urban areas or wide open sites, they make it possible to hoist and distribute loads high and far. The Potain brand is a global leader with its multiple ranges of MCT and MDT topless cranes, MR, MRH and MCH luffing jib cranes and large MC, MD and MD Maxi hammerhead cranes that can also be customized to match special applications.

While technologies integrated in the cranes continues to progress, it is important to realize the maintenances to ensure the safety of the material and the humans working with it.



Manitowoc Direct

In order to help you on a daily basis, we have set an intranet on which you can find numerous technical documents relating to our products.

To find them, go on our Manitowoc website, at www.manitowoc.com, click on “Manitowoc Direct”, log in or create your account.

The screenshot shows the Manitowoc website's header and a large pop-up window titled "Manitowoc Direct Request Access".

Header:

- Home icon
- Manitowoc logo
- GROVE
- POTAIN®
- NATIONAL CRANE
- SHUTTLELIFT
- Search icon
- MANITOWOC DIRECT** (highlighted with a red box)
- FIND A DEALER

Pop-up Window:

Left Side (Buttons):

- MANITOWOC DIRECT** (button with lock icon)
- LOGIN** (button with lock icon)
- REQUEST ACCESS** (button with lock icon)

Right Side (Content):

For access to :

1. **Grove CONNECT | Potain CONNECT** – contact your [local dealer](#) OR your local Manitowoc Support.
2. On-line Parts Ordering (**GPX**) & Warranty Claims (**GWX**) – contact your local Manitowoc Support.

* Mandatory fields

Personal Information

First Name*	<input type="text"/>
Last Name*	<input type="text"/>
Phone	<input type="text"/>
Mobile Phone	<input type="text"/>
Fax	<input type="text"/>
Professional email*	<input type="text"/>
Professional email confirmation*	<input type="text"/>

Company Information

Company Name*	<input type="text"/>
Address 1*	<input type="text"/>
Address 2	<input type="text"/>
City*	<input type="text"/>
State/Provience*	<input type="text"/>



Accueil > Manitowoc Direct > Potain > Parts Support

Manitowoc Direct

■ Potain

Flash Produit (FP)

Guide Produit (GP)

▶ Parts Support

Parts Support Level 2

Tower Parts and Service
handbooks and Warranty
procedures

■ Customer Support

EnCORE Partner Manuals

North American Distributor
Contact Information Update

Request for Return or Credit

Customer Support Bulletins

Bulletins Pièces

Bulletins Pièces

Bulletins Tarification

Bulletins Service après-vente

Bulletins Formation

Équipes des centres de contact
nord-américains

Policy Manuals

Potain Parts Support

Contact +33(0)472815151 | Europetower.parts@manitowoc.com

Show All

■ Parts Support

Peripheriques - Peripheral

- Anémomètre-Anemometer - XLS (880.6 KB)
- Balsage aviation - Hazard Lighting - XLSX (868.8 KB)
- Lot VISU-VISU set - XLS (93.7 KB)
- Projecteurs - Projectors - XLSX (2 MB)

Électrique - Electrical

- Câbles électriques - Electric cables - XLSX (1 MB)
- Climatisations - Air conditioners - XLSX (583.6 KB)
- Combinateurs Pièces de rechange - Joysticks spare parts - XLSX (7.6 MB)
- Flash et Klaxon - XLSX (1.4 MB)
- Matériel_Electrique-Electrical_Material - XLSX (738.6 KB)
- Prises_et_Connecteurs-Plugs_and_Connectors- - XLSX (4.7 MB)

Mecanique - Mechanic

- Boulons_Notece-Bolts_Instruction - XLSX (193.2 KB)
- Butée et Linguet - Hook Safety Catch and Ball Thrust Bearing - XLSX (2 MB)
- Cables métalliques _Wire ropes - XLSX (1.4 MB)
- Lubrifiants_mécanisme-Mechanism_Lubricants - XLSX (70.3 KB)
- Roulements_et_Joints - Bearings_Seals - XLSX (708.2 KB)
- Trains de transport_Transport axles - XLSX (19.8 MB)

Anti-collision

- MC602 - XLSX (55.5 KB)
- MC603 - XLSX (1.6 MB)
- Top Site - XLS (826.4 KB)
- Top Zone - PDF (443.1 KB)
- TT2 - XLS (1.1 MB)
- TT3 CCS - HUP - XLSX (397.5 KB)

Radio commande-Remote control

- Catalogue_pieces_rechange - Spare parts catalog - XLSX (52.2 MB)
- Radiocode retrofit - RRC retrofit - XLSX (1.4 MB)

Accueil > Manitowoc Direct > Potain > Tower Parts and Service handbooks and Warranty procedures

Manitowoc Direct

■ Mes applications

■ Grove

■ Potain

Flash Produit (FP)

Guide Produit (GP)

Parts Support

Parts Support Level 2

Potain e-Academy

▶ Tower Parts and Service
handbooks and Warranty
procedures

Tower Parts and Service handbooks and Warranty procedures

Show All

■ Policy-manuals

- 02BR-Tower-crane-parts-and-service-handbook-2017-12-0-DE - PDF (1.3 MB)
- 02BR-Tower-crane-parts-and-service-handbook-2017-12-0-EN - PDF (1.3 MB)
- 02BR-Tower-crane-parts-and-service-handbook-2017-12-0-ES - PDF (1.3 MB)
- 02BR-Tower-crane-parts-and-service-handbook-2017-12-0-FR - PDF (1.3 MB)
- 02BR-Tower-crane-parts-and-service-handbook-2017-12-0-IT - PDF (1.2 MB)
- 02BR-Tower-crane-parts-and-service-handbook-2017-12-0-PT - PDF (1.3 MB)

■ Warranty-Procedures

- Garantieprocedure_NL-V11 - PDF (491.8 KB)
- Garantieverfahren Produktreihe Turmdrehkrane EURAF_DE-V11 - PDF (440.7 KB)
- Procedimento Garantia_PT-V11 - PDF (521.3 KB)
- Procedimiento Garantizado_ES-V11 - PDF (405.1 KB)
- Procedura - Garantía_IT-V11 - PDF (513.6 KB)
- Procedura Gwarancyjna_PL-V11 - PDF (629.8 KB)
- Procédure Garantie - FR-V11 - PDF (408.1 KB)
- Warranty Procedure_EN-V11 - PDF (435.3 KB)
- Положения гарантийного обслуживания_RU-V11 - PDF (533 KB)



Why choose the genuine part?

> Expert knowledge - Manufacturer's warranty

Only the manufacturer has an overall view of the product and, by means of its technical proficiency, it guarantees total compatibility. Generic aftermarket parts meet just a few basic criteria and can modify the characteristics of the machine.

> Advantages of the genuine parts

- ✓ Safety,
- ✓ Manufacturer warranty,
- ✓ Service life,
- ✓ Traceability,
- ✓ High-quality technical support.



> The risks of the adaptable part

- ✗ Modification of the characteristics of the crane,
- ✗ Security problems with serious human and material risks,
- ✗ Premature wear of other components,
- ✗ Increase in maintenance costs and immobilization of equipment,
- ✗ Cancellation of the "Manufacturer" warranty,
- ✗ No recourse possible against the manufacturer.



Fixing angle



Control panel



Mast section

Small gain, big risk !

- Prod 08 22 EN

If you require more information, please contact your usual correspondent or contact us via e-mail address :
europetower.parts@manitowoc.com – Non-contractual document, reproduction prohibited



CONSUMABLES



Greases for maintenance

To increase the service life of your equipment, Manitowoc recommends the use of these products for routine and regular maintenance.

Standard quality for slewing ring bearings G2 type

E-01032-51*	Cartridge 400 g	H-01032-54
	Cartridge 400 g new pump	84066032
	Can 5 kg	G-01032-53



High-quality for slewing ring bearings GM type *

T-61032-74*	Cartridge 400 g	J-61032-65
	Cartridge 400 g new pump	84066033
	Can 20 kg	U-61032-75



Aerosol for slewing ring gears and teeth P type

P-01032-60*	Spray 400 ml	S-01032-63
-------------	--------------	------------



Specially selected for fish joints by pins ATD type

N-61032-23*	Can 1 kg	T-61032-05
	Can 5 kg	84066107
	Cartridge 400 g	84137291



Specially selected for topping up grease in reducer gear S00 type

H-12032-52*	Tube 250 g	82016145
	Can 5 kg	J-12032-53
	Can 50 kg	K-12032-54



Specially selected for topping up grease in reducer gear G0 type

K-12032-08*	Can 1 kg	L-12032-32
	Can 18 kg	P-12032-12



Grease for crane-driver lift electric cables

TCL	Tube 100 g	84055311
-----	------------	----------



Grease for crane-driver lift pinions and racks

TCL	Cartridge 400 g	84055312
-----	-----------------	----------

Brushes

60 mm	Z-14811-76
30 mm	K-06444-69



*Technical code - not to order. Please ask for the reference on the right side.



Oils for maintenance

Selected, tested and adapted to the Potain cranes

Oil for reduction gears – RC Type		Symbol
Q-12032-13*	Can 5 litres	W-61032-77
	Can 25 litres	S-12032-15
Oil for reduction gears – HR Type		
H-61032-87*	Can 5 litres	84055632
	Can 25 litres	84108905
Oil for reduction gears – HRA Type		
Q-61032-94*	Can 5 litres	84055662
	Can 25 litres	84108906
Oil for reduction gears - RSC Type		
S-61032-96*	Can 5 litres	84055634
	Can 25 litres	T-61032-97
Oil for reduction gears construction hoist		
TCL	Can 5 litres	84055313



* Technical code – not to order. Please ask for the reference on the right side.



Hydraulics oil for maintenance

Selected, tested and adapted to the Potain cranes

Hydraulic oil for telescoping hydraulic units:			Symbol
E Standard Type E-12032-26*	Can 5 litres	84108903	
	Can 25 litres	G-12032-28	
F Type (Extreme weather conditons) B-01032-48*	Can 5 litres	84108902	
	Can 25 litres	D-01032-50	

Can also be used for braking devices

Hydraulic oil for hydraulic units Hup, IGO, HD cranes:			
I Type P-61032-47*	Can 5 litres	84108904	
	Can 25 litres	Q-61032-48	



* Technical code – not to order. Please ask for the reference on the right side

Scan or click to access online support
Or contact your usual Potain agent .





Paints for maintenance

Selected, tested and adapted to the Potain cranes

Primer

Primer beige aerosol	Spray 400 ml	82021847
Primer **	Can 23,7 Kg	84062805
Primer Glycero**	Can 1 kg	P-65034-24
Primer hardener	Can 3,7 kg	84062806
Primer Zinc	Can 1 kg	82011766
	Can 15 kg	84062558



Solvent

Dry solvent	Spray 400 ml	84138294
Paint thinner X400 - Glycero	Can 5 l	F-11034-99
Thinner primer	Can 25 l	B-68034-24
Lacquer thinner PU/THES	Can 25 l	84077707

Hardener for polyurethane lacquer PU/THES

	Can 5 kg	84012719
--	----------	-----------------

Yellow paint for cranes supplied after 1992

SPU FIN THES**	Can 13,5 kg	84061724
Glycero**	Can 1 kg	K-65034-66



Paint for daytime hazard lighting**

Red PU/THES**	Can 13,5 kg	84061399
Red Glycero**	Can 1 kg	N-65034-69
White PU/THES**	Can 13,5 kg	84061397
White Glycero**	Can 1 kg	R-65034-95

**** Use with the appropriate hardener!**



Paints for maintenance

Selected, tested and adapted to the Potain cranes

Red paint

SPU FIN THES**	Can 13,5 kg	84061416
Glycero**	Can 1 kg	K-67034-74

POTAIN grey lacquer *:

Aerosol	Spray 400 ml	Z-67034-18
PU/THES: for cranes supplied after 2000	Can 13,5 kg	84061420
Glycero	Can 1 kg	L-66034-71
	Can 25 Kb	W-67034-16



POTAIN galvanised lacquer *:

Matt Paint Aerosol (Old-age effect)	Spray 500 ml	82013254
Gloss Paint Aerosol (New-age effect)	Spray 400 ml	84121855



POTAIN yellow lacquer 92 * :

Aerosol	Spray 400 ml	82028322
---------	--------------	-----------------



White lacquer:

Aerosol	Spray 400 ml	84116146
Polyurethane lacquer	Can 13,5 kg	84063456
Glycero	Can 1 kg	M-65034-68

Blue lacquer:

Aerosol	Spray 400 ml	82001191
---------	--------------	-----------------



Red lacquer:

Aerosol	Spray 400 ml	S-67034-35
---------	--------------	-------------------



* Essential in the inspection vehicles!



Our grease guns

Because lubrication is an essential aspect for the maintenance of your cranes, discover our range of grease guns

Electric grease gun

For precise and easy lubrication, even under difficult conditions



Battery : 12 Volts Li-ion. Charger included.

Pressure : 562 bars

Battery life : ±7 cartridges with a single charge

Hose : 91 cm

Charging indicator

Manual grease gun

Provides ergonomic lubrication, with its magnetic holder



Pressure : 800bars

Weight : 1,4 kg

2,5cc for each pump



The kit includes 1 adapter for screw-on cartridge (1) and 10 sealing lids for traditional cartridges (2).

Discover our automatic and motorized lubricator solutions, as well as all our lubrication products in our [quick reference catalogue](#).

References

Grease guns		
Electric grease gun		84155029
Additional battery		84155031
Manual grease gun kit		84066027
Screw-on cartridge adapter (1)		84066028
Set of 10 traditional cartridge sealing lid (2)		84066029
Grease cartridges 400g	G2	GM
Traditional	H-01032-54	J-61032-65
Screw-on	84066032	84066033



Automatic Grease cartridges

Extend the lifetime of your slewing rings thanks to an efficient greasing:

- Greasing no less than 3 months,
- 6 bars pressure,
- Mounting possibilities on other greasing points,



For optimal longevity, we recommend that you use a reinforced connection.

> Kits for GME and GMA range

Complete grease cartridge

- Programming by LCD display,
- LED lights with indicators,
- Reusable drive system,
- Delivered with a 120cm³ cartridge and Battery Pack.



Reinforced connection

- Recommended for all uses, especially in the event of vibrations or collision risks with other parts, when the cartridge are offset.

Refills (*batteries included*)

- 120cm³: ~ 3 months
- 250cm³: ~ 6 months

> For GMEs only

Complete chemical grease cartridge

- Time stretch duration by switch, simplified use,
- Compact system: 125cc cartridge, no fitting or battery needed.

> For old GMA (HD/GTMR)

Special retrofit kit

- For automatic greasing system (complete system and connection to be ordered separately)





Automatic Grease cartridges

References

Articles

Complete greasing cartridge (with cartridge 120cm ³ , batteries and support)	J-01458-97
Battery Pack	82007821
Complete greasing cartridge cold countries (with cartridge 120cm ³ and batteries support) Delivered without batteries (Lithium 3 x AAA 1.5V)	84116687
Complete chemical greasing cartridge	84031284
Reinforced connection (regular greasing cartridge, GMA kit or Very cold weather)	K-01458-98
Specific retrofit kit for GMA/HD/GTMR	N-51458-02
Reducing adapters	M10x100 Q-75375-51 M10x150 V-75375-56
	M8x125 W-75375-57 Elbow fitting X-75375-58

Refills

Refills classical grease (delivered with support + batteries)	120 cm ³	Q-62505-40
	250 cm ³	H-62505-56
Refills Cold countries grease	120 cm ³	84116686



Motorized lubrication also available, please have a look at our dedicated SPN.

Scan or click to access online support

Or contact your usual Potain agent





Motorized lubrication

Simplify your lubrication operations

> Standard system for slewing ring lubrication

- Compact greasing system only operates during a slewing motion (programming),
- Up to 20 greasing points simultaneous,
- Tank contains 1,2 kg of grease lasts for 3 to 6 months (depending of the use),
- 4 grease cartridges are included in the kit,
- Supply voltage: 0 – 60VCD*,
- Temperature range: -35 à +70°C,



* For use on CCS Crane : please order in addition an electrical adaptator kit.

> Optional: toothing lubrication**



10 modules toothing kit

- Tothing lubrication is ensured by a greasing pinion and a pumping element fixed on the unit; connected together by a hose,
- While operating, only the pinion face which is in contact with the slewing ring ensures the lubrication,
- This pinion is fixed by means of a support to be welded on the towerhead.

** Please contact your usual agent.

Scan or click to access online support

Or contact your usual Potain agent.





Motorized lubrication

Simplify your lubrication operation



Unit with 4 greasing points



References

Kits

Kit 4 Internal Greasing Points	K-21995-45
Kit 6 Internal Greasing Points	L-21995-46
Kit 8 Internal Greasing Points	M-21995-47
More 8 points	Contact us

Miscellaneous

4 grease cartridges	J-61032-65
CCS Adaptator kit	84004522

For some tower cranes, we propose grease recuperator kits to ensure the cleanliness of towerhead and security of accesses.



In addition, we also propose a range of grease cartridges for tower cranes. Please see our Spare Parts News.

Scan or click to access online support
Or contact your usual Potain agent.






ATD Grease for fish joints

Safety and operation ensured for a long time !

This product is complying with a strict Potain specifications sheet, ensuring a controlled wear of fish joints by pins, subject to use at each assembly.



> Characteristics

- Designed to increase pin's mast assembling lifetime,
- Fitting and dismantling of the pins facilitated,
- To be used at each assembly,
- Contains additives to protect the surfaces of the assembled parts, even under high pressure.

> Advantages

- Protects against corrosion and fretting corrosion,
- Waterproof and adapted to off shore locations,
- Slows down the ovalization of the borings and the wearing,
- Very strong adhesive force on the metallic surfaces,
- Excellent thermal stability : can be used from -25°C to + 50°C and can be stored from -40°C to + 60°.

References

Specially selected for mast fish joints

Type ATD	Can 1 kg	T-61032-05
Type ATD	Can 5 kg	84066107



Lubricant for steel ropes

Extends the life of your wire ropes

Only for the hoisting and luffing steel ropes.

> Advantages

- Deposits a protective oil film which resists to the mechanical pressures naturally generated by the external fittings (pulleys, drums...),
- Reduces frictions, abrasive wear and fouling,
- Protects against rust and corrosion,
- Penetrates quickly and deeply in steel rope to lubricate strands and cores,
- Weather resistance,
- Extends life of heavily loaded wire ropes, pulleys, drums, guides, pins and rollers.



> Operating instruction

- For effective application, we recommend you clean the wire rope carefully before processing,
- Spray a thin layer in several times for optimal protection,
- For ease, apply the spray when the wire rope is being wound on the drum.



Recommended by Potain for the maintenance of
wire ropes of its cranes

Grease Aerosol
Spray 400 ml LC

P-61032-70



- Lube 08 22 EN



Lubricants analysis kits

Optimize your maintenance costs

➤ Why making regular maintenances ?

To extend the reliability and service life of your cranes, Potain recommends to realize maintenances on your crane :

- **Preventive maintenance** : To anticipate and prevent malfunctions or broken parts. It's based on regular maintenance (routine operation) and detailed maintenance (inspection of key components),
- **Corrective maintenance** : Repairs or change some parts of the crane, arrived to its end-of-life, to ensure security and performance.




➤ Lubricants analysis kits: to monitor lubricants quality

Scheduling preventive maintenance programs helps to keep your costs down. Potain has developed a lubricant analysis kit, in 2 version :

- Oil analysis kit : reduction gears and hydraulic units,
- Grease analysis kit : slewing rings and reduction gears.

In addition to your current preventive maintenance programs, lubricant analysis makes it possible to monitor the quality of oils and greases in service and therefore to detect the state of wear or degradation of lubricated parts.



For more information, please check our product guide 626 on our website.



- Kolb 08 22 EN



Lubricants analysis kits

References

Analysis kit

Oil analysis kit	84052659
Grease analysis kit	84052660

Grease analysis kit



Oil analysis kit



The kit includes, whatever the type,

- Sample bottle
- Hose
- 2 stickers to identify the sample and the descriptive file
- A pre-paid envelop to send the sample and the demanding file to a specialized and dedicated laboratory .

Scan or click to access online support
Or contact your usual Potain agent.





Universal greasing kit

Maintain your crane!

If your crane is equipped with a battery-operated motorized lubrication system, the grease cartridges must be replaced periodically to ensure proper lubrication of the slewing ring. Potain also recommends greasing the hoist rope periodically to increase its service life.



> Characteristics

- 4 refills for automatic grease nipples,
- 1 spray of P grease for ring teeth,
- 1 spray of LC grease for hoist rope,
- One kit covers: 6 months maintenance for a GMA, 3 months for a GME.

> Advantages

- Better availability: fewer job site stops,
- You save money in the medium term: fewer replacements of expensive components,
- Optimized resale value.



You can record your maintenance operations in our reference maintenance logbook: V-85985-92

References

Universal lubrication kits for cranes with automatic greasing	
Complete kit for GME or GMA	84129896

- Kitu 11 22 EN



Miscellaneous consumables

Selected, tested and adapted to the Potain cranes



Anti-seize compound*

Spray 400 ml K-01035-78



Anti-seize agent*

Spray 400 ml E-01035-27



Anti-seize paste copper

Tube 200 gr L-15031-98

Anaerobic fixation

Bottle 75 ml R-12035-36

Cyanoacrylate adhesive*

Bottle 20 gr H-12035-05

Rust converter

Can 1l 84139193

Anti-corrosion

Can 650ml 82032659

Brake cleaner

Spray 500ml 84126744



Repair kit glass bonding

Tube 412 gr 82020617

Mastic adhesive

D8 Roll 6 m V-02031-32



Insulating adhesive tape*

Set 10 insulating adhesive tapes B-61031-43

* Essential in the inspection vehicles!

Scan or click to access online support



Or contact your usual Potain agent.

If you require more information, please contact your usual correspondent or contact us via e-mail address :

europetower.parts@manitowoc.com – Non-contractual document, reproduction prohibited



SAFETY



Anticollision: Why equip your cranes ?

Increasingly complex job site configurations, tight delivery times, architectural constraints...All of these factors can put the smooth running of your job site, at risk !

Working **safely**, **minimize** unforeseen expenses and **increase productivity** are the keys to SUCCESS.

The anti-collision system meets these requirements by offering a simple and cost-effective solution:

➤ A secure job site!

- Multiple cranes working at the same time? Overflight zones to avoid ? All these conditions create a risky work environment.
- As a machine operator, protecting people who work or gravitate around the job site is your responsibility.

➤ Controlled costs!

- Damage caused by an accident is severe and the resulting financial losses can be considerable.
- Now update the check using a dedicated system !

➤ Improved productivity!

- A safe environment, optimized travel speeds, controlled decelerations and stops.
- The crane driver can safely concentrate on their main tasks.

Scan or click to access to our anticollision offer
Or contact your usual Potain agent.






Anticollision system TT3

Anticollision system

An anti-collision system*, meeting the regulations in effect, for the control of work areas and the management of interference for all types of tower cranes.

> Characteristics

- Travelling sensor with several registration points (several RFID tags),
- Inter-crane management / configuration of prohibited areas,
- Hook height management in prohibited areas,
- If TT3 "shunted" in the CCS, visual indication on the screen,
- Black box (one year of memory) and possible filters:
 - Faults, sensor by sensor
 - Recording of access (identifiers / dates / access)
 - Weathervanes
 - Neutralizations



> Advantages

- Carryover of all the previous generation systems functionalities: anti-collision (up to 16 cranes), prohibited areas (up to 30), management of different radios (frequencies),
- Intergenerational compatibility of systems (including with TT1),
- Compatibility with Supervisor 603 (optional),
- Software update by USB key only.

- New color touch screen
- Day or night mode display setting
- Wind speed visible directly on the neutralization box.
- Possibility of neutralization:
 - Prohibited zones zone by zone,
 - Crane-by-crane interference.
- If number of cranes ≥ 16 , possibility to connect another radio.
- Remote setting of systems between cranes.





Anticollision system MC602

For all brands and types of cranes

➤ Characteristics

- New display: indicator and anti-collision (height, range, load, moment, wind speed, pre-alarm and anti-collision alarm, interference zone),
- Universal computer box for all types of cranes (models and brands),
- Translation encoder with anemometer signaling,
- Recording of events and possible failures.

Display



➤ Key point

- Prevents the danger of collision, limits the crane working zone (Prohibited overslewing of buildings, aerial lines...),
- Driving aid system,
- Controls the interferences between cranes,
- Remote monitoring,
- Communication with the previous Top tracing I and II.

➤ Reliability and simplicity

- Digital technology, transmission by CAN bus network,
- Processing unit protected in a tight housing - IP65,
- Crane driver information (dangerous areas),
- Calibration and adjustment protected by a password,
- Pre-wired input/output function, Harting connector,
- Optional: signal lamp in case of malfunctioning, shunt box.



Calculator

➤ Compatibility

- MC603,
- TOP TRACING 2,
- TOP TRACING 3.

Scan or click to access online support
Or contact your usual Potain agent.





Anticollision system MC603

Anticollision system



➤ Advantages

- Compliant with European standards EN 14439 and EN 17076,
- Certified as PLC according to ISO13849,
- Simple installation and intuitive calibration,
- Software updated using USB drive,
- FREE software upgrades,
- Individually neutralizable prohibited zones.

➤ Designed for which cranes ?

- System adaptable to all crane brands:
 - GME : Saddle jib and luffing jib,
 - GMA.

➤ Compatibility

- MC602,
- TOP TRACING 2,
- TOP TRACING 3.

➤ Crane with CCS or CAN bus

- The system connects directly to the CAN bus interface of the crane.
- For other technologies, the system is connected to the crane via an interface box.

➤ Options

- Supervisor, wireless neutralization box for collector cranes.



Shunt box



Calculator



Interface

Scan or click to access online support
Or contact your usual Potain agent.





Supervisor for anti-collision systems


A monitoring tool for your remote job sites

➤ Characteristics

- Compatible with all anti-collision systems distributed by Potain (up to 16 cranes),
- Graphic view of the job site in real time,
- Event recorder (visualization of sensor faults, radio, wind*, etc.),
- Data export,
- Remote connection via an IP address,
- Option: Radio connection.

➤ Pack components

- 1 PC,
- 1 screen,
- 1 connection box.



* Excluding Top Tracing II

References

Articles

Complete pack Supervisor

84076986

Scan or click to access online support

Or contact your usual Potain agent.





Hoisting and trolley wire rope

High-performance ropes at competitive prices



> Advantages

- Performance: lifespan increased by at least 25%*
- Versatility: compatible with all your machines (CCS or not).
- Service: Stock available and advice adapted to your applications.
- Traceability: Identification by coloring an outer strand.

* Compared to a regular range

> Hoisting wire rope range

- **PREMIUM** 24 strand compacted rope, 7 steel wires, steel metal core.
- **HIGH PERFORMER/E** 25 strand compacted rope, 7 steel wires, steel metal core.
- **HIGH PERFORMER/S** 29 strand compacted rope, 7 steel wires, steel metal core.

> Trolley wire rope range

- **PREMIUM** 6 strand compacted rope, 19 steel wires, textile core.
- **HIGH PERFORMER** 9 strand compacted rope, 7 steel wires, steel metal core.



Scan or click to access online support
Or contact your usual Potain agent .




- Caba 03 23 EN



Hydraulic tensioner

For slewing ring bolts

The hydraulic tensioner is an essential tool to ensure the perfect tightening of the bolts of the slewing ring of your GME.



- The tightening of the slewing ring bolts must comply with strict rules
- The use of hydraulic tension bolts on GME cranes (implementation during 2000) requires the use of a specific torque tools.
- Potain offers two different types of tensioners, for M20 to M27 bolts with a single high-pressure hand pump.

> Hand pump characteristics

- Hose length 3m with rapid connector.
- Oil pressure gauge.
- The unit is supplied in a box.



> Tensioners*

- Bolts M27.
- Bolts M20, M22 and M24.

* For other sizes, Please contact us.

References

Hand pump

Complete pump with box

U-64435-37

Tensionners

Bolts M27

82017094

Bolts M20, M22 and M24

82017093

Scan or click to access online support
Or contact your usual Potain agent



- Teng 08 22 EN



Aircraft warning package

*More complete, more competitive !**

> Advantages

- Works on all crane types: saddle jib and luffing jib,
- Autonomous operation: 48 h for night lighting / 12 h for daytime lighting,
- A single 230/400V dual-voltage control panel for all types of lights (LI/MI for night and MI for daytime),
- Low power consumption (LED technology),
- IP66 ingress protection.

> Standard package

	Night	Day
H < 45 m Total crane	Low intensity <ul style="list-style-type: none"> ▪ Overmoulded single-piece unit, 3 x 32 Cd LED. ▪ Connection with moulded cable, no risk of corrosion. ▪ Control box with integral photoelectric cell. 	Medium intensity <ul style="list-style-type: none"> ▪ 1 medium intensity light with 6 bi-colour LED floodlights: <ul style="list-style-type: none"> ▪ Day: white 20,000 Cd (type A), ▪ Night: red 2,000 Cd (types B and C). ▪ Integral GPS module for day/night switching 
45 m < H < 150 m	Medium intensity <ul style="list-style-type: none"> ▪ 1 medium intensity light with 2,000 Cd. ▪ Adjustable flash rate: <ul style="list-style-type: none"> ▪ Type B: 20 to 60 flashes per min, ▪ Type C: light permanently on. ▪ Integral GPS module for day/night switching. 	
H > 150 m	High intensity light: contact us for details.	



All our systems are provided with an emergency control panel and the supports, cables and accessories needed for installation. The supply voltage is 48 V DC.

For any other requests, contact us. We will give you a custom quotation.

*Our aircraft warning lights comply with the requirements of the OACI and the FAA. Approval of the system by the local civil aviation authority remains the responsibility of the customer.

Scan or click to access online support
Or contact your usual Potain agent.





Slewing ring bolts

Check or regularly change your bolts

> Follow the manufacturer recommendations



- **Every 8 years or 16 000 hours working hours:** Systematic pre-ventive exchange of the slewing ring bolts untreated (black's) every 8 years or after 16000 hours of operation of the machine, 1st term reached.
- **Systematic exchange** of the slewing ring bolts by change of the slewing ring of the crane, unless specific instructions from Potain.
- **Every year** : Verification of the tightening of the slewing ring bolts, following the instructions of the service guide provided with the crane.
- **Every 12 years or 24 000 hours working hours:** Systematic pre-ventive exchange of the slewing ring bolts treated (grey's) every 12 years or after 24000 hours of operation of the machine, 1st term reached.

> Characteristics

- Specially selected and adapted to your crane,
- Define according to specific standards that meet,
- Precise specifications imposed to all our suppliers,
- Traceability for all bolts.



In addition, we offer a rust protector for HR slewing bolts.

Protector for HR bolt

Spray 650ml

82032659



Scan or click to access online support
Or contact your usual Potain agent.





Slewing ring seal kit

This slewing ring seal kit is for use with GMA-GME cranes of the Potain brand.



> Advantages

- You order the entire assembly and only replace those items used,
- Compact, all-in-the box,
- You always have everything you need for your operations.

> Characteristics

- The kit includes 5 airtight seals with lengths of 2 x 7 meters:
 - Z-61031-41
 - V-61031-15
 - Q-61031-79
 - Q-61031-56
 - G-15031-02
 - 2 x 20 g bottles of Cyanolite
 - H-12035-05 glue
 - 1 lidded box 84034044

> Selecting a profile

To determine which seal profile you need for your slewing ring, please consult the table below

Reference	Profile	On millimeter paper (*)
Z-61031-41		
V-61031-15		
Q-61031-79		

Reference	Profile	On millimeter paper (*)
O-61031-56		
J-15031-04		
G-15031-02		
H-15031-03		

References

Kit of 5 airtight seals

Complete kit 5 seals

Included box with lid

Included : Cyanolite glue bottle

84034143

84034044

H-12035-05

- Kit 08 22 EN



STRUCTURE





Upgrade chassis

Improve safety and ergonomics !

POTAIN, in cooperation with the Fédération Nationale des Travaux Publics (French National Federation of Public Works), has worked on improving safety and ergonomics when unloading the packages and fitting the V60A chassis for 2 m masts.

> Main improvements

- Handling: Creation of slinging points and guide handles,
- Packaging of struts + half-bearers allow safe unloading with less handling and more space on the job site.
- Basic mast section: Creation of a fixed, central catwalk and two foldable side catwalks to facilitate the pin-connection of the struts, platforms with four angles facilitating the pin-connection of the mast section, and tubes used as a guard rope for harnesses,
- Pins from the top: Improved accessibility for mast section/half-bearer pin connections,
- Two beams allowing the basic mast section to be stabilized in a vertical position on a ballast block.



References

Chassis kit

S41A – Kit upgrade

84010255

V60A– Kit upgrade

84000349

V63A– Kit upgrade

84005134

Scan or click to access online support



Or contact your usual Potain agent.

- Kchb 08 22 EN



Support plates

Ensure the stability of your crane



Let's contribute together to the protection of the nature by using recycled materials !

Made from composite material, the support plates proposed by Potain are a better substitute for wooden plates which are usually used for supporting GMA cranes or mobile crane.

> Characteristics

- Very strong: no splitting,
- Very long lifespan: do not rot or absorb moisture,
- Easy to clean,
- Excellent Quality/Price ratio compared with wood,
- Very light (density 1) and easy to manipulate with their handles.



> Different shapes

- Standard Rectangle models,
- Standard square models,
- Standard round models.



In order to determine the support plate type, consider the maximum reaction under your crane bearing (indicated by the constructor) as well as the permissible maximum pressure of the ground where the crane will be erected.



If the ground pressure is not $\geq 2,5 \text{ daN/cm}^2$, please contact us.

* Please consult us for any other dimension at your convenience.

Scan or click to access online support
Or contact your usual Potain agent.





Support plates

References

Rectangle models

750 x 1000 mm	50 mm	38kg /piece	4	Z-82985-60	Igo 15, 18, 21, 22, 26, 30, M 21, MA 21
1000 x 1200 mm	60 mm	72kg /piece	4	W-82985-58	Igo 32, 36, 42, 50, GTMR 331C, Hup 32-27, 40-30, Hup M 28-22
1000 x 1200 mm	80mm	96kg /piece	4	D-83985-22	Igo 32, 36, 42, 50, GTMR 331C, Hup 32-27, 40-30, Hup M 28-22
1000 x 330 mm	80 mm	32kg /piece	4	B-84985-24	

Square models

400 X 400 mm	50 mm	8kg / piece	2	S-86985-70	
600 x 600 mm	40mm	15kg / piece	4	V-82985-57	Igo 10, 11, 13, M 14
600 x 600 mm	60 mm	21,5kg / piece	4	X-86985-98	
600 x 600 mm	60 mm	28,5kg / piece	4	J-86985-39	
750 x 750 mm	50 mm	28kg / piece	4	F-83985-93	
800 x 800 mm	40mm	25,5kg / piece	4	E-86985-12	
800 x 800 mm	50 mm	32kg / piece	4	C-86985-56	
800 x 800 mm	60 mm	38kg / piece	4	Z-86985-76	
1400 X 1400 mm	100mm	200kg / piece	4	82029208	Igo T70, T85A, T130, HDT 80, GTMR 386 B

Round models

Ø 700	50 mm	19kg / piece	4	82008919	
Ø 800	50 mm	25kg / piece	4	82003476	Igo 10, 11, 13, 15, 18, 21, M 14, M 21
Ø 900	40mm	38kg / piece	4	A-86985-54	
Ø 900	60 mm	38kg / piece	4	B-86985-55	Igo 22, 26, 30, Hup M 28-22
Ø 1000	80 mm	62kg / piece	4	W-85985-24	Igo 32
Ø 1200	60 mm	68kg / piece	4	82003475	Igo 36, 42, 50, GTMR 331C, Hup 32-27, 40-30
Ø 1200	80mm	95kg / piece	4	03142474	Igo 36, 42, 50, GTMR 331C, Hup 32-27, 40-30




Screw jacks protection

The support plate protection preserves the screw thread from dust and concrete.

> Characteristics

- The setting of support plates remains easy even after several construction sites usages.
- The assembly is possible on a crane in operation.
- Compatible with chassis
 - ZC4230
 - ZD4230
 - ZD463
 - ZX6830



References

Screw jacks protection

Set of 4 protections (for one chassis)

84058203

Scan or click to access online support
Or contact your usual Potain agent.





Double rope pulling grip with swivel

Make your rope changes safer

These new generation cable pulling grips with central swivel are ideal for safe wire ropes replacement. Usable for ropes without termination and with diameters greater than 8 mm.

They meet the obligations of European regulations, in particular the "Machinery" Directive 2006/42/EC.



References

Rope diameter	
8/10	84063553
10/15	84051421
15/20	84051422
20/25	84063554
25/30	84063564
30/35	84063565

Scan or click to access online support
Or contact your usual Potain agent.





K mast fixing angle sets

Ensure the safety with genuine components

For more flexible management of your equipment, we propose equipped fixing angles in the form of a kit.

> Characteristics

The kit is composed of :

- 1 kit of 4 unequipped fixing angles
- 1 fishplate kit
- 1 pin kit



Please find a summary table for our offer below:

Old equipped fixing angle sets*	Commercial name
84138805	P24A/P42A
84138803	
U-61109-57	P41A
V-61109-58	
82031776	P61B
82031775	
82028042	P62B
82028041	
82049603	P800B
82049609	
82049598	P850A
H-20680-29	
B-18680-61	P854A
W-14108-17	
84136912	P880
84136913	

Unequipped fixing angle set
84138886
W-61109-59
82031909
82028835
82025958
82014499
84071651
84136916

Fishplate kit
84070143
84070143
84070144
84070144
84070144
84070145
84070145
84142895

Pin kit	Pin version
84070146	Standard
84070147	Tirax
84070146	Standard
84070147	Tirax
84070148	Standard
84070149	Tirax
84070150	Standard
84070151	Tirax
84070152	Standard
84070153	Tirax
84070154	Standard
84070155	Tirax
84070154	Standard
84070155	Tirax
84142896	Standard
84142897	Tirax



* The former equipped Part Number cannot be ordered anymore ! The fishplate kit cannot be ordered alone.



L mast fixing angles sets

Ensure the safety with genuine components

We propose you our full range of sets of fixing angles for L mast, with or without pin!



> You have pins and want to reuse them?

Order only a set of bare fixing angles and economize the price of pins !



> You need pins?

We propose a kit containing:

- 8 pins,
- 4 shafts,
- and 4 safety-pins

> You want an equipped set of fixing angles ?

You can order a set of bare fixing angles **and** a pins kit.

Please find below a chart that summarizes our offer

Commercial name	Former P/N for set of fixing angles with pins*
P12B	B-77109-81
P12C	Z-30110-90
P12D / P16A	P-75110-31
P12E / P20A	A-22101-39
P12ER / P16E / P21A	N-82662-81
P20A / P21A SP	Q-23101-11



New P/N for fixing angles without pin
84063457
84063458
84063459
84063460
84063461
84107953

New P/N for kits pins + shafts
84063462
84063463
84063463
84063464
84063464
84107954



The former equipped Part Number cannot be ordered anymore !



Tirax 80

Specially designed and manufactured by Potain for pin-connection of Potain K masts, the Tirax 80 allows pins to be safely fitted and removed, silently and without effort.

Pins installed and removed in only five stages:

1. Engage the jaws on the gripping head
2. Tighten the jaws on the pin head
3. Pull the pin
4. Remove the pin
5. Open the jaws and remove the Tirax 80



> Characteristics

- Portable tool consisting of a hydraulic cylinder with gripping jaws and a handle, ensuring safe transport.
- Compatible with
 - 50 mm (1.6 m mast),
 - 60 mm; (2 m mast),
 - 80 mm (2.45 m mast) pins.
- Portable hydraulic unit connected by sleeved hose,
- Uses special pins equipped with gripping heads.



> Capacities

- Maximum traction: 21 t,
- Maximum operating pressure: 700 bar,
- Traction time per pin, 6 seconds approx.,
- Hydraulic unit supply: 400 V 50 Hz, 480 V 60 Hz,
- Hydraulic unit power: 1,5 kW.



References

Article

Complete Tirax

84118324



1.2m K masts


Our new offer for K200 masts!

A new K mast offer 1.2m cross-section for MDT city cranes (up to MDT159) equipped with a 1.6m section towerhead, particularly suitable for installation in restricted areas.

per A complete range ...


10m and 5m monoblock masts section. Up to 4 masts in the same tractor-trailer train

KM247A
KM249A
KM247E
KM249E



Inverted connecting mast K20/K40

Fixing angles



P23A/P41A



P24A/P42A




R24A/R42A



... to maximize the performance of your cranes

Example :

Hook heights
MDT 159 → 45 m jib / C50



For confined spaces, such as elevator shafts, there is a short axis version in standard and tirax versions.



Mast pin securing device

POTAIN is committed to safety!

- Mast pins securing device (diameters 50/60/80 mm)



This lockable system prevents the risk of pins falling when the crane is dismantled.

- Anti-vibration tool to remove pins diameter 40 and 60 mm



The use of an unsuitable axle, spindle or tool creates a safety risk.



This system prevents the risk of hand crushing and vibration when the axles are difficult to remove.

Other tools will soon be added to this safety equipments!

References

Equipment for erectors and technicians

Mast pins securing device	84103688
Tool to remove pins diameter 40mm	84015112
Tool to remove pins diameter 60mm	84015111



PERIPHERICAL PRODUCTS



Vision cabins POTAIN*

The original manufacturer cheaper than the adaptable !



Cabin V140C



Cabin V140L



Cabin V140 SX

> Major advantages

- **Original part:** Safety, quality, durability... It fully meets our requirements and allows optimal operation of your machine!
- **Manufacturer's warranty:** Guaranteed machine warranty, technical support, service and parts availability for a minimum of 10 years ... Work with peace of mind!
- **Cabin conforms to the EC standard:** Security, electrification, and glazing.

Why take risks when safety is within reach?

Offer the best for your crane at a competitive price!

*Different models available according to your crane type.

Scan or click to access online support
Or contact your usual Potain agent.






Retrofit kit for Cab Visor

for non-equipped Ultra View cabs

The kit contains all the elements necessary for installation as well as an installation manual of a visor on the cab. It is not fitted for Ultra View cabs, already equipped with visor.

➤ Characteristics

- Optimization of water flow
- Better visibility in rainy weather
- Durability (painted stainless steel visor)
- Easy installation
- Aesthetic: fits perfectly with the cab design



Degressive net price from 10 kits ordered !

References

Article	
Cab Visor kit	84119773

Scan or click to access online support
Or contact your usual Potain agent .



- Vib 08 22 EN



Cab heating

Winter is coming....

Has your crane driver already complained about the poor condition of his cab heating? Don't wait for the breakdown and anticipate the request by installing a quality heating device right now !

> Characteristics

- Specially selected for the crane cabs.
- Size : 253 x 253 x 164 mm.
- Weight : 5,5 kg.
- Low noise level: 50dB.
- Power: 2000 W.
- With ventilation function for the summer.
- Tridirectional heating.
- Robust metal housing.



3 position button

1. Ventilation (summer),
2. Heating and regulated ventilation,
3. Stop.



Room thermostat control

References

Heater

Cab heater

Q-15418-19

Scan or click to access online support

Or contact your usual Potain agent.





Dialog Wind Anemometer

Prevent the overturning of your cranes !

Mandatory for the prevention of the risk of overturning of cranes under the effect of the wind, it is an essential safety element. Entirely digital, Dialog Wind is reliable and robust, and is certified by CETIAT.



> Sensor

- Non-oxidizing tight bearings,
- Electronic card protected by double varnishing,
- Polyurethane cables with compound-filled connector link.

> Indicator

- Adjusting of the alarm and prealarm thresholds by means of access code,
- Fixing by «non-slip» magnets,
- 4 button keypad with signal lamps + buzzer,
- Button for testing the correct working order,
- Choice of speed unit: km/h, m/s or miles/h
- Internal buzzer and display for fault signalling and identification.



> Alarm block

- Adjustable luminous alarm frequency (5 W lamps),
- Programmable alarm bell (110 dB siren at 1 m),
- Fixing by «non-slip» magnets,
- Protecting by roller bar

> Options

- Repeater: Additional display box (wire link, cable 60m)
- Radio repeater : For cranes with collector, we propose a solution with radio repeater, pack including: sensor + alarm block + main display + repeater display,
- Giant Vision display : see our SPN [« Giant display XXL »](#).



Dialog Wind Anemometer

References

Complete pack configured without Collector

Sensor + alarm block + main display + cables	H-68416-10
Sensor (alone)	J-68416-11
Cup holder set (alone)	Z-68416-25
Display (alone)	N-68416-15
Alarm block (alone)	P-68416-16

Complete pack – Crane configured with Collector

Sensor + alarm block + main display + repeater display	F-71406-54
--	------------

Options

Repeater: Additional display box (wire link, cable 60m)	Q-68416-17
---	------------

Scan or click to access online support
Or contact your usual Potain agent.





Giant display XXL

For all types of cranes

The Giant display XXL indicates the wind speed on a large LED screen

➤ Characteristics

- Display composed of 3 digits of 7 segments of big size (100 mm height) + unit label
- Tightness : IP 65.
- Mains supply : 24VDC (19-36v).
- Temperature : -20 à +70°C.



➤ Advantages

- Compatible with Potain Dialog Wind and any system using: 4-20 mA, 0-5 V and frequency anemometer sensor,
- Visible by all people on the site up to 50 meters,
- Limits the amplified danger of accidents during extreme weather conditions,
- Complying with European standards,
- Quality material, shock-proof and resistant to vibrations,
- No maintenance.

References

Not CCS Crane	
Giant display XXL	84002612
CCS Crane	
Giant display XXL	84042786
Power box	84043689
Bottom crane display	Contact us
MR Refresh Cranes (MRxx8)	
Giant display XXL	Contact us

Scan or click to access online support “Anemometer” associated :

Or contact your usual Potain agent




**NEW**

Jobsite lighting for GME

Improve the safety of your job sites with LED spotlights

> Characteristics

- Type LED spotlights - Reduced power consumption,
- Configuration On masts (photo no. 1) or/and on jib (photo no. 2).
Folding for transport or telescoping position,
- Electrical power 300 W, 240 V,
- Lighting intensity 39,000 Lumens,
- Power supply 230 – 400 V,
- Control Single switch (at the bottom) or two-way switch (at top and bottom).



We can simulate the lighting of your job site by software to optimize the number of spotlights required.

> What about GMA cranes ?

Find our complete range (GME and GMA), all the models available and information concerning our product support





Advertising lighting

Improve the signage of your jobsites!

Designed for cranes, palisades, facilities, bungalows....

> Magnetic version

- Installation without screws and without drilling,
- No impact on wind resistance,
- Light, soft, flexible, thickness < 1 mm,
- Customizable sizes.



> Tarpaulin version

- Light, soft, flexible,
- Customizable sizes,
- Fastening to all supports thanks to its rings.
- Use only on solid walls, not on crane masts

> Plate version

- Quick and easy installation (screws and nuts),
- Wind resistance conforms with the crane's notices,
- Lightweight, less than 30 Kg,
- From 2,86 m² to 5m² customizable, for an installation on the counter-jib, depending on your crane type and your needs.



> Advantages

- Light emitting technology: Power supply via 230V DC enclosure equipped with a programmable clock,
- 100% Made in France and 100% Customizable,
- Low power consumption: 3x less than LED technology,
- In compliance with the French standards on light pollution,
- 20,000-hour lifespan,
- Temperature range: - 30° to + 45 ° C.

- Ecpd 02 23 EN



Driving Camera

Improve the safety on your jobsite

> Characteristics



- Low consumption,
- 22x optical zoom, autofocus, wireless zoom pedal,
- Operating temperature: -30°C to + 65°C,
- Simple and quick assembly, no additional loading device,
- Insensitive to the wind and shocks and vibrations resistant.
- 3 years warranted

> Trolley tower crane kit

- 10" or 13" screen,
- Solar pannel,
- Transmitter integrated,



> Luffing jib tower crane kit

- 10" or 13" screen,
- Electric tilt system: perfect image stability,
- 75m cable,



Delivered in its own protective suitcase !

NEW

> Recorder

- 7 days recording duration on 128GB micro SD (supplied)
- preset to work with the camera
- quick installation



References

Driving camera kits	10 " Display	13" Display
Trolley tower crane kit (MD/MDT Crane)	84128766	84129678
Luffing jib tower crane kit (MR Crane)	84128781	84129679
Recorder		84136944



CAB 'In

Internal crane-driver lifting equipment



- Developed in collaboration with the company GEDA,
- Option to retrofit the existing mast sections: contact us.

The internal crane-driver lifting equipment for Potain mast sections is compatible with all K mast sections.

> Characteristics

- Mast sections prefitted at the factory,
- Hoisting speed up to 24 m/min,
- Load capacity: 200 kg/ 2 person,

> Advantages

- Installation carried out at the same time as the crane and alongside the access ladders,
- No extra transport and storage costs,
- Optimal management of the mast section fleet, compatible with:
 - All K mast sections (1.6 m, 2 m and 2.45 m) with new and old access.
 - All current mast section bases (fixing angles, chassis and cross-shaped bases).

> Safety

- Arrival/departure platforms enclosure.
- Upper and lower sensors on the lift cab for safety when in use.
- 360° visibility from the crane-driver lifting equipment interior for inspecting the mast sections.
- Drive unit maintenance from the inside of the crane-driver
- Optional : Kit for acceptance of commissioning and periodic inspection.



In France: in accordance with recommendation R.495. From January 1, 2019, motorized access is mandatory if the crane cab requires an ascent of more than 30 m.

- Cable 06 22 EN



CCS Tool kit

References

CCS Tool kit

Complete CCS Tool kit (all articles under included)			84054165
Backpack (w/o tools)	84054154	Peack CAN cable	84016291
Crimping tool harting	84053003	Connection cable	84018979
Extraction tool	84024379	Diagnostic cable	84010624
Insertion tool	84053004	Female contact harting	84006891
Crimping tool SCM/CCT	84053005	Male contact harting	84006917
Crimping die	84053008	Socket CCS Display	03142169
Extraction tool AMP MT	04157406	Contact CCS Display	80003367
Extraction tool AMP JPT	04157382	AMP JPT Contact 0,5 - 1,0	03142253
Screwdriver	84053011	AMP MT Contact 1,0 - 2,5	03142436
End	84053012	AMP JPT Contact 1,0 - 2,5	03142435
Tightening tool	84062863	USB Stick	84058247

Scan or click to access online support
Or contact your usual Potain agent.





CCS Tool kit

Cranes equipped of CCS technology require specific tools to realize maintenance.

To ensure you to have all the needed tools with you to realize the operation, we propose you a specific adapted backpack. Ergonomic and practical, it includes all essential tooling troubleshooting CCS cranes.

- Backpack - 1 PC
- Crimping tool harting - 1 PC
- Extraction tool - 1 PC
- Insertion tool - 1 PC
- Crimping tool SCM/CCT - 1 PC
- Crimping die - 1 PC
- Extraction tool AMP MT - 1 PC
- Extraction tool AMP JPT - 1 PC
- Screwdriver - 1 PC
- End - 1 PC
- Tightening tool - 1 PC
- Peack CAN cable - 1 PC
- Connection cable - 1 PC
- Diagnostic cable - 1 PC
- Female contact harting - 100 PC
- Male contact harting - 100 PC
- Socket CCS Display - 1 PC
- Contact CCS Display - 100 PC
- AMP JPT Contact 0,5 - 1,0 - 100 PC
- AMP MT Contact 1,0 - 2,5 - 100 PC
- AMP JPT Contact 1,0 - 2,5 - 100 PC
- USB Stick - 1 PC



* For further information on the content of this kit (tool details, references...), please refer to 'CCS Tools Catalogue' (available upon request)





Jib lifting beam

Reinforce safety on your site

Handling and shifting crane elements are delicate exercises which can cause accidents. To minimize the danger and to improve safety on your site, Potain proposes a jib lifting beam.




> Characteristics

- Jib lifting beam for round bar of 40mm to 170 mm.
- Max. load per lifting beam: 17500daN.
- Weight per lifting beam: 30kg.

> Advantages

Secures the slinging operation, especially for double tie bar lines.

The beam separates the chains allowing room for the tie bars to lift without catching the chains.



References

Article	
Jib lifting beam	84003496


- Pald 08 22EN



Mast pins securing devices

POTAIN is committed to safety!

- Mast pins securing device (diameters 50/60/80 mm)



This lockable system prevents the risk of pins falling when the crane is dismantled.

- Anti-vibration tool to remove pins diameter 40 and 60 mm



The use of an unsuitable axle, spindle or tool creates a safety risk.



This system prevents the risk of hand crushing and vibration when the axles are difficult to remove.

Other tools will soon be added to this safety equipments!

References

Equipment for erectors and technicians	
Mast pins securing device	84103688
Tool to remove pins diameter 40mm	84015112
Tool to remove pins diameter 60mm	84015111





Remote Controls

Our remote controls are taking into account the features of each of the mechanisms of your cranes, either recent or old ones.

> Characteristics

- Improve the productivity of your sites : driving from a distance,
- Better control of handling operations and better occupation of the staff,
- For optimum safety, systematic stop of movements in progress in case of interruption or loss of the radio link.

> 4 Remote control ranges

Approved for every country and complying with the E.U. directives, there is different type of remote controls depending of the range :

- **PRB 1:** For small cranes (overhead travelling cranes).
- **PRC:** For range GMA (HDT and GTMR)
- **PRS or PRM:** For range GME (MD, MDT and MR)
- **V3 and CCS:** For ranges GMA and GME (Igo T, MCT and MDT)

Our remote controls can be supplied with or without indicator, at your choice.

> Composition



When the controls of a crane are through use of a component not authorized by the manufacturer, responsibility can not be accepted in case of damage caused "on" or "by" the crane.



Remote control accessories

> CCS Transmitter protection cover



- Protection against scratches and dirt.
- Opening for battery.

> Carrying harness



- More ergonomic than the classic belt.
- Reduce musculoskeletal disorders of the neck and back.
- Help to drive with more precision.
- Adjustable.
- Compatible with the following transmitters:



References

Articles	
CCS transmitter protective cover	84129220
Carrying Harness	84129221



Walkie-talkies

Better communication between crane driver and slinger

Those walkie talkies, durable and practical, are designed to fit to all the professional contexts. This specific model has been selected by our own after sales service that uses it regularly in its interventions on cranes.

➤ Characteristics

- Power 500 mW, a range of up to 10 km, with 18 h battery life,
- “hands free” function : communication is triggered by voice,
- “Monitoring” function : you can hear without being heard,
- 16 channels and 121 private codes sub-channel for frequency setting,
- Scan function to detect busy channels.
- Emergency button : cuts off automatically all conversations to make the call.

➤ Kits composition

- 2 transmitters - receivers
- 2 rechargeable batteries NiMH
- 1 dual charger (2 USB micro connections)
- 2 belt clips.



References

Article

Walkie-talkie pack

82005259

New battery 2.75 Ah



Up to 40% more capacity*



This new battery fully complies with the original manufacturer's specifications covering of our whole range of cranes equipped with a NOVA transmitter or GL using the battery P-63418-95 or 84043425.

> Characteristics

- Capacity : 2.75 Ah,
- Technology : Nickel –Metal Hydride (Ni-MH),
- Nominal voltage : 3.6V.

> Advantages

- Up to 40% more capacity,
- A preferential tariff for a quantitative order,
- Compatible with the fast charger N-63418-94.



Only POTAIN batteries guarantee the correct operation of our transmitters. When using batteries sold elsewhere than in our network these can damage the electronics of our transmitters and in no case, we would be held responsible for the damage caused.

References

Battery and charger

Batteries 2.75 Ah

84043425



SERVICES



Document reissue

For Potain GMA or GME cranes type*

Systematically supplied with the new cranes, they also can be supplied on request for old crane models.

They are carried out in perfect accordance with the crane composition: Type, serial number, desired language, country where the crane operates, or wind standard used are necessary. Here is the list of the document that can be reprinting:

➤ **Complete set of manuals: Fitting + operation + spare parts**

- Paper version**
- USB version**
- Complementary reactions



➤ **EC certificate of conformity duplicate**



Useful when recording the maintenance operations.

➤ **Neutral maintenance logbook**



Useful when recording the maintenance operations.

➤ **Red bag for set of manuals**

- For GME
- For GMA



*Subject to the availability of the translation in the requested language. This table only concerns records ordered after-sales, outside the sales channel of new cranes.

**Also order one of these references if you need a crane inspection book (Kranprübuch) for Germany and Poland.

References

Articles

Complete Set	Paper version	E-62985-31**
	USB version	84070396**
	Complementary reactions	84143055
EC certificate of conformity		84118659
Neutral maintenance logbook		V-85985-92
Red bag	For GME	84121774
	For GMA	84121775



Goodies

Passionate about the POTAIN brand?

Find all our promotional items to offer a unique gift!



> Scale model

Estafette POTAIN: **84147165**

> Key rings

Technician's Van: **84152824**

POTAIN Logo: **84152825**

> Clothes

Men's Polo: 100% Organic cotton

Size	S	M	L	XL	XXL	XXXL
P/N	84152833	84152834	84152835	84152836	84152837	84152838

> POTAIN Models



The presentation of our models is available via this
QR Code






Potain CONNECT+



> Potain CONNECT+

With Potain CONNECT+, Make it easy to follow your fleet, real time, 24/7

- Improve the productivity
- Improve safety and environmental impact
- Develop your activity





CraneSTAR®
Diag



POTAIN®
CONNECT+

This solution is available for all your cranes CCS cranes, GME or GMA, and MRxx8.

✓ Access to the web portal

- Real-time geolocation
- Remote diagnostics
- Remote parameter modification
- Management of maintenance alerts and notifications

Reports:

Maintenance notification + Maintenance plan

Crane

Configuration crane activity

Wind

Fault codes

Transmission of reports/email

- Crane user and fleet management
- Integration of crane fleet data in any other ERP

✓ Application on smartphone

- Local diagnostics
- Software update (Hup and Hup M)
- Consultation of ex-works documentation + updates


For 3 years or more Potain CONNECT+ subscription (*CraneSTAR Diag running contract included*), the new **Potain CONNECT+ modem** is for free.

Installation takes only few minutes !


Example 1



Example 2



Example 3



★ Retrofit request



Potain Gold offer

Reduce your costs and preserve the environment by choosing our offer « GOLD ».

- Reconditioned parts, tested and checked by our suppliers, guaranteeing you the same standards as a new part.
- Offer valid on a list of specific items, in limited quantities*.
- Attractive price*.
- 12 months warranty.

* Contact us



Scan or click to access our genuine Part SPN,
Or contact your usual Potain agent.



If you require more information, please contact your usual correspondent or contact us via e-mail address : europetower.parts@manitowoc.com –
Non-contractual document, reproduction prohibited - Golc 12 22 BN



« Standard Repair » motors

According to the motor type, Potain proposes 2 replacement solutions for a defective motor:

> New Motors

- According to the specifications sheet of the original motors («first mounting»),
- Complying with the last technical developments in force,
- Large updated stock, immediately available.



> « Standard Repair » motors

Before



After



- A perfect quality level, comparable to the new product,
- Complete dismantling and systematic checking of all components.
- Checking of the insulation, measurement of the leakage current and continuity test of the windings.
- Boring of the bearings, bleaching of the collector rings.
- Degreasing, cleaning, shot blasting, stoving or rewinding.
- Systematic replacement of all worn parts by original parts and bearings.
- Optimum balancing, quality grade: G.6.3.
- Final inspection without load and with load on a specific test bench.
- Complying with the last technical developments in force.
- Only one constraint: the defective motor must be returned within one month



We also propose a « Standard Repair » on gearbox and some frequency inverters.

Scan or click to access online support
Or contact your usual Potain agent.



- Echf 06 22EN



Training Academy Potain

Improve and enhance the skills of your teams

➤ Skills and knowledge of your team

The skills and knowledge of men and women in the field are essential to the performance and sustainability of a construction company.



Aware that knowledge of assembly, troubleshooting and the tools inherent in the use of a crane is of great importance for technicians working on construction sites, Potain also offers to train your teams in the various crane trades.

The Potain training center has been created in 1970 on its historic site of La Clayette. From now on called Potain Academy, the center is now located near Lyon, in St Pierre de Chandieu, on the same site as the spare parts stores.

➤ The Academy

Equipped with 5 permanently mounted Potain cranes (3 GMA and 2 GME), the Potain Academy offers training in crane driving, assembly, or repairs, for its customers and Potain dealers.

Periodically, the Academy receives new models for a shorter duration to provide new product training to dealers purchasing their first crane.



If you want more information, don't hesitate to see the Academy's brochure, on our website, or scan the QR Code:



[Potain Academy EN](#)



- Acad 12 22 FR

Regional headquarters

Americas

Milwaukee, Wisconsin,
USA
Tel: +1 414 760 4600

Europe and Africa

Dardilly, France - TOWERS
Tel: +33 4 7218 20 20

APAC

Shanghai, China
Tel: +86 21 6457 0066

Middle East and India

Dubai, UAE
Tel: +971 4 8862677

Shady Grove,
Pennsylvania, USA
Tel: +1 717 597 8121

Wilhelmshaven,
Germany - MOBILE
Tel: +49 (0) 4421 294 0

Singapore
Tel: +65 6264 1188

This document is non-contractual. Constant improvement and engineering progress make it necessary that we reserve the right to make specification, equipment, and price changes without notice. Illustrations shown may include optional equipment and accessories and may not include all standard equipment.

