

Wire Rope Specifications

MLC150-1

Luffing Jib No. 135A on
Boom No. B20:350

Maximum Required Parts of Line - Drum 1												
Boom Length		Luffing Jib Length Meters (Feet)										
Meters	Feet	21,3 (70.0)	24,4 (80.0)	27,4 (90.0)	30,5 (100.0)	33,5 (110.0)	36,6 (120.0)	39,6 (130.0)	42,7 (140.0)	45,7 (150.0)	48,8 (160.0)	51,8 (170.0)
21,0	68.9	4	4	4	3	3	3	2	2	2	2	2
24,0	78.7	4	4	3	3	3	3	2	2	2	2	2
27,0	88.6	4	4	3	3	3	3	2	2	2	2	2
30,0	98.4	4	3	3	3	3	3	2	2	2	2	2
33,0	108.3	4	3	3	3	3	2	2	2	2	2	2
36,0	118.1	3	3	3	3	3	2	2	2	2	2	2
39,0	128.0	3	3	3	3	2	2	2	2	2	2	1
42,0	137.8	3	3	3	3	2	2	2	2	2	2	1
45,0	147.6	3	3	3	2	2	2	2	2	2	1	1
48,0	157.5	3	3	2	2	2	2	2	2	2	1	1

Maximum Required Parts of Line - Drum 3												
Boom Length		Luffing Jib Length Meters (Feet)										
Meters	Feet	21,3 (70.0)	24,4 (80.0)	27,4 (90.0)	30,5 (100.0)	33,5 (110.0)	36,6 (120.0)	39,6 (130.0)	42,7 (140.0)	45,7 (150.0)	48,8 (160.0)	51,8 (170.0)
21,0	68.9	3	2	2	2	2	2	2	1	1	1	1
24,0	78.7	2	2	2	2	2	2	1	1	1	1	1
27,0	88.6	2	2	2	2	2	1	1	1	1	1	1
30,0	98.4	2	2	2	2	1	1	1	1	1	1	1
33,0	108.3	2	2	2	1	1	1	1	1	1	1	1
36,0	118.1	2	2	1	1	1	1	1	1	1	1	1
39,0	128.0	2	1	1	1	1	1	1	1	1	1	1
42,0	137.8	1	1	1	1	1	1	1	1	1	—	—
45,0	147.6	1	1	1	1	1	1	1	1	1	—	—
48,0	157.5	1	1	1	1	1	1	1	1	—	—	—

Wire Rope Specifications

MLC150-1

Luffing Jib No. 135A on
Boom No. B20:350

Wire Rope Lengths (includes all luffing jib lengths)					
Boom Length		Hoist Line Drum 1		Hoist Line Drum 3	
Meters	Feet	Meters	Feet	Meters	Feet
21,0	68.9	260	840	195	630
24,0	78.7	260	840	195	630
27,0	88.6	275	890	195	630
30,0	98.4	280	910	195	630
33,0	108.3	290	940	195	630
36,0	118.1	290	950	195	630
39,0	128.0	290	950	195	630
42,0	137.8	305	990	190	620
45,0	147.6	305	990	190	620
48,0	157.5	305	990	190	620

Note: Hoist line lengths given in table will allow hook to touch ground. When block travel below ground is required, add additional rope equal to parts of line times added travel distance. Hoisting distance or line pull may be limited when block travel below ground is required.

Hoist Reeving for Load Block - Drum 1				
No. Parts of Line	1	2	3	4
Maximum Load - kg	13 430	26 860	40 290	49 300
Maximum Load - lb	29,600	59,200	88,800	108,800
Maximum Load per Part of Line - kg	13 430	13 430	13 430	12 325
Maximum Load per Part of Line - lb	29,600	29,600	29,600	27,200

Hoist Reeving for Load Block - Drum 3			
No. Parts of Line	1	2	3
Maximum Load - kg	9 070	18 140	27 210
Maximum Load - lb	20,000	40,000	60,000
Maximum Load per Part of Line - kg	9 070	9 070	9 070
Maximum Load per Part of Line - lb	20,000	20,000	20,000

Wire Rope Specifications

MLC150-1

Luffing Jib No. 135A on
Boom No. B20:350

Wire Rope Specifications	
<u>Rotation Resistant Wire Rope - 5:1 Safety Factor</u>	
Hoist Line:	
26 mm (Drums 1 & 3):	
Wire Rope with Spelter Button and Pad Eye	
Right Hand Lang Lay	
Minimum Breaking Strength = 67 130 kg (148,000 lb)	
Approx. Weight = 3,41 kg/m (2.28 lb/ft)	
No Load Dia = 26,44 mm (1.041 in) to 26,78 mm (1.054 in)	
Ref: 80123747, 80120441	
<u>Optional Wire Rope - 3.5:1 Safety Factor</u>	
Hoist Line:	
26 mm (Drums 1 & 3):	
Wire Rope with Spelter Button	
Right Hand Regular Lay	
Minimum Breaking Strength = 48 170 kg (106,200 lb)	
Approx. Weight = 2,89 kg/m (1.94 lb/ft)	
No Load Dia = 26,44 mm (1.041 in) to 26,78 mm (1.054 in)	
Ref: 80123752	

Maximum Spooling Capacities	
Drum 1: (Front)	26 mm Wire Rope - 5 Layers - 344 m (1,130 ft)
Drum 3: (Auxiliary)	26 mm Wire Rope - 4 Layers - 175 m (575 ft)
7 m (23 ft) is deducted from maximum spooling capacities for 3 dead wraps per drum on drum 1.	
5 m (15 ft) is deducted from maximum spooling capacities for 3 dead wraps on drum 3.	

Refer to Drum and Lagging chart **No. 9830-A** and Load Block Reeving in the Operator Manual.

Refer to Block Overhaul Weights chart **No. 9825-A** for minimum weight required for block lowering.

Warning: Free fall operation is limited to 6 710 kg (14,800 lb) per part of line when lowering load with free fall clutch/brake pedal. Hydraulic power shall be used for full line pull. *Permanent brake damage could occur allowing the load to lower uncontrolled.*