



Wire Rope Specifications

Liftcrane - Boom No. 79

MAX-ER 2000
On 2250

European Standards

Wire Rope Lengths								
Boom Length		Whip Line Drum 5				Hoist Line Drum 9		Maximum Required Parts of Line
		1 Part		2 Part				
Ft.	Meters	Ft.	Meters	Ft.	Meters	Ft.	Meters	
120	36.6	300	91	425	130	3800	1158	28
140	42.7	340	104	500	152	4000	1219	26
160	48.8	380	116	550	168	4200	1280	24
180	54.9	420	128	625	191	4400	1341	22
200	61.0	460	140	675	206	4400	1341	20
220	67.1	500	152	725	221	4400	1341	18
240	73.2	540	165	800	244	4400	1341	16
260	79.2	580	177	850	259	4400	1341	14
280	85.3	620	189	925	282	4400	1341	12
300	91.4	660	201	975	297	4400	1341	12
320	97.5	700	213	1025	312	4400	1341	10
340	103.6	740	226	1100	335	4400	1341	8
360	109.7	780	238	1150	351	4400	1341	8

Note: Hoist line and whip line lengths given in table will allow hook to touch ground. When block travel below ground is required, add additional rope equal to parts of line times added travel distance. Hoisting distance or line pull may be limited when block travel below ground is required.

Hoist Reeving for Main Load Block						
No. Parts of Line	8	10	12	14	16	18
Maximum Load - Lbs.	277,600	347,000	416,400	485,800	555,200	624,600
Maximum Load - kg	125 920	157 400	188 880	220 360	251 830	283 310
No. Parts of Line	20	22	24	26	28	
Maximum Load - Lbs.	694,000	763,400	830,700	891,400	900,000	
Maximum Load - kg	314 790	346 270	376 800	404 330	408 200	



Wire Rope Specifications

MAX-ER 2000

Liftcrane - Boom No. 79

European Standards

On 2250

Wire Rope Specifications	
Hoist Line:	28 mm Wire Rope Right Hand Lang Lay, Rotation Resistant Minimum Breaking Strength = 179,400 Lbs. (81 370 kg) MCC Part No. 719425 Approx. Weight = 2.76 Lbs. Per Ft. (4.11 kg/m) Minimum Breaking Strength Required = 173,500 Lbs. (78 700 kg) No Load Dia. = 1.124 in. (28.55 mm) to 1.146 in. (29.11 mm)
Whip Line:	25 mm Wire Rope Right Hand Lang Lay, Rotation Resistant Minimum Breaking Strength = 139,400 Lbs. (63 230 kg) Maximum Load = 27,700 Lbs. (12 560 kg) per line MCC Part No. 719428 Approx. Weight = 2.10 Lbs. Per Ft. (3.12 kg/m) Minimum Breaking Strength Required = 138,500 Lbs. (62 820 kg) No Load Dia. = 1.010 in. (25.65 mm) to 1.033 in. (26.24 mm)
	OR
	7/8 in. (22 mm) 2160 N/mm ² Wire Rope Right Hand Lang Lay, Rotation Resistant Minimum Breaking Strength = 109,600 Lbs. (49 710 kg) Maximum Load = 20,000 Lbs. (9 070 kg) per line MCC Part No. 719414 Approx. Weight = 1.65 Lbs. Per Ft. (2.46 kg/m)
Other 7/8 in. luffing hoist wire ropes specified on 2250 luffing jib rigging are not allowed.	

Maximum Spooling Capacities	
Drum 9: (Hoist Line)	28 mm Wire Rope - 11 Layers - 4,334 Ft. (1 321m)
Drum 5: (Whip Line)	25 mm Wire Rope - 6 Layers - 1,104 Ft. (336m) with 19 in. (483 mm) Dia. Lagging
	7/8 in. (22 mm) Wire Rope - 7 Layers - 1,157 Ft. (353m)
21 Ft. (6m) is deducted from maximum spooling capacities for 3 dead wraps on Drum 9, 16 Ft. (5m) on Drum 5. 7/8 in. wire rope cannot be used as luffing hoist on MAX-ER 2000.	

Refer to Drum and Lagging chart **No. 8195-A**.