






## New aircraft warning package\*

### More complete, more competitive!

#### The main advantages:

- Works on all crane types: saddle jib and luffing jib.
- Easy installation.
- Autonomous operation: 48 h for night lighting / 12 h for daytime lighting.
- A single 230/400V dual-voltage control panel for all types of lights (LI/MI for night and MI for daytime).
- Low power consumption (LED technology).
- IP66 ingress protection.

#### Our standard package:

		Night	Day
Total crane height	H < 45 m	<p><b>Low intensity</b></p> <ul style="list-style-type: none"> <li>▪ Overmoulded single-piece unit, 3 x 32 Cd LED lights.</li> <li>▪ Connection with moulded cable, no risk of corrosion.</li> <li>▪ Control box with integral photoelectric cell.</li> </ul> 	<p><b>Medium intensity</b></p> 
	45m < H < 150 m	<p><b>Medium intensity</b></p> <ul style="list-style-type: none"> <li>▪ 1 medium intensity light with 2,000 Cd.</li> <li>▪ Adjustable flash rate:                             <ul style="list-style-type: none"> <li>• Type B: 20 to 60 flashes per min,</li> <li>• Type C: light permanently on.</li> </ul> </li> <li>▪ Integral GPS module for day/night switching.</li> </ul> 	<ul style="list-style-type: none"> <li>▪ 1 medium intensity light with 6 bi-colour LED floodlights:                             <ul style="list-style-type: none"> <li>• Day: white 20,000 Cd (type A),</li> <li>• Night: red 2,000 Cd (types B and C).</li> </ul> </li> <li>▪ Integral GPS module for day/night switching</li> </ul>
		<p><b>H &gt; 150 m : High intensity light: contact us for details.</b></p>	

*For any other requests, contact us. We will give you a custom quotation.*

All our systems are provided with an emergency control panel and the supports, cables and accessories needed for installation. The supply voltage is 48 V DC.

*\* Our aircraft warning lights comply with the requirements of the OACI and the FAA. Approval of the system by the local civil aviation authority remains the responsibility of the customer.*

**To determine the part numbers to order, scan or click to access our online support:**

*Or contact your usual Potain agent .*

