

# Drum and Lagging Chart

## MLC150-1

Application	Drum Number and Location	Drum Part Number	Type Of Drum	Drum Diameter	Drum Width	Wire Rope Size
<b>LIFTCRANE</b>						
<b>Hoist</b>	Drum 1 (Front)	80115483 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
		80115477 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
<b>Whip or Luffing</b>	Drum 2 (Rear)	80115488 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
		80115486 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
<b>Auxiliary (Optional)</b>	Drum 3	80115492	Grooved	454 mm (17-7/8 in.)	724 mm (20-1/2 in.)	26 mm
<b>CLAMSHELL - LIMITED DUTY</b>						
<b>Closing</b>	Drum 1 (Front)	80115483 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
		80115477 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
<b>Holding</b>	Drum 2 (Rear)	80115488 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
		80115486 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm