




Liftcrane Boom Capacities

Boom No. 82 or 22EL
67 860 kg Counterweight
Rating Over End of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements



999 SERIES 1

LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and do not exceed 75% of a static tipping load over end of machine with crawlers blocked. Capacities based on structural competence are denoted by an asterisk (*). Capacities indicated by (b) require 5 670 kg minimum weight.

Upper boom point capacity for liftcrane service with single part whip line is 13 380 kg or 26 760 kg with two part whip line. When boom butt mounted auxiliary drum is used, capacity with single part whip line is 9 070 kg or 18 140 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

76.2m boom length requires only the middle two sheaves in lower boom point. All other sheaves must be removed from lower boom point.

Weight of jib, all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves, is considered part of main boom load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with


gantry up. Drive and idler tumblers must be properly blocked so that centerline of tumblers becomes tipping fulcrum. Swing is limited to that sector shown on Operating Range Diagram
No. 8224-A. Refer to boom rigging **No. 195459** (No. 82) or **No. 195890** (No. 22EL) and Wire Rope Specification chart **No. 8223-A.** Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 8 585 mm crawlers, 1 219 mm treads, 3 124 mm retractable gantry, 9 144 mm live mast, 20 part boom hoist reeving, boom support straps or four 35 mm boom pendants and 67 860 kg counterweight.

Maximum Boom and Jib Lengths Lifted Unassisted Over End of Blocked Crawlers			
WITHOUT BOOM CATWALKS		WITH BOOM CATWALKS	
Boom Length	Jib No. 134	Boom Length	Jib No. 134
(a) 76.2m	—	(a) 76.2m	—
73.2m	—	(b) 73.2m	—
70.1m	—	70.1m	—
67.1m	18.3m	67.1m	15.2m
64.0m	24.4m	64.0m	24.4m
Load block, hook and weight ball on ground at start. (a) Upper boom point cannot be used on 76.2m boom. (b) Machine must be equipped with lowerworks jacking cylinders.			




67 860 kg Crane Counterweight
6 Side Boxes - 1 Center Box

Consult jib chart for jib capacities.
Upper boom point cannot be used when jib is attached.

Boom Catwalks Deduct
Deduct 300 kg from capacities when boom catwalks are attached.

Deduct From Capacities When Jib Is Attached	
Jib Length	Jib No. 134
9.1m	1 220 kg
12.2m	1 590 kg
15.2m	1 950 kg
18.3m	2 310 kg
21.3m	2 770 kg
24.4m	3 220 kg



Liftcrane Boom Capacities

Meets
ANSI B30.5
Requirements


Boom No. 82 or 22EL
67 860 kg Counterweight
Rating Over End of Blocked Crawlers
No Travel - Limited Swing

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
21.3m (70 Ft.) BOOM			
4.9	82.8	23.5	204 600 *b
5.0	82.5	23.5	200 100 *b
5.5	81.1	23.4	183 100 *b
6.0	79.7	23.3	168 700 *b
7.0	77.0	23.1	145 700 *b
8.0	74.2	22.8	128 000 *
9.0	71.3	22.5	114 000 *
10.0	68.4	22.1	99 500
11.0	65.5	21.6	84 500
12.0	62.5	21.1	73 500
13.0	59.3	20.5	64 800
14.0	56.1	19.8	57 900
15.0	52.7	19.0	52 100
16.0	49.1	18.1	47 300
18.0	41.3	16.0	39 700
20.0	31.9	13.2	33 900
24.4m (80 Ft.) BOOM			
5.2	83.0	26.6	193 100 *b
5.5	82.2	26.5	182 700 *b
6.0	81.0	26.4	168 400 *b
7.0	78.6	26.2	145 400 *b
8.0	76.2	26.0	127 700 *
9.0	73.8	25.7	113 700 *
10.0	71.3	25.3	99 700
11.0	68.8	24.9	84 700
12.0	66.2	24.5	73 600
13.0	63.5	24.0	64 900
14.0	60.9	23.4	57 900
15.0	58.1	22.8	52 200
16.0	55.2	22.1	47 300
18.0	49.1	20.4	39 700
20.0	42.4	18.4	33 900
22.0	34.5	15.7	29 400
24.0	24.5	11.9	25 700
27.4m (90 Ft.) BOOM			
5.8	82.5	29.6	173 900 *b
6.0	82.0	29.5	168 300 *b
7.0	79.9	29.3	145 200 *b
8.0	77.8	29.1	127 500 *
9.0	75.6	28.9	113 600 *
10.0	73.4	28.6	99 900
11.0	71.2	28.2	84 800
12.0	69.0	27.8	73 700
13.0	66.7	27.4	65 000
14.0	64.4	26.9	58 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
27.4m (90 Ft.) BOOM			
15.0	62.0	26.4	52 200
16.0	59.6	25.8	47 300
18.0	54.5	24.4	39 700
20.0	49.1	22.7	34 000
22.0	43.2	20.7	29 400
24.0	36.4	18.2	25 800
26.0	28.3	14.9	22 800
30.5m (100 Ft.) BOOM			
6.1	82.7	32.6	165 600 *b
7.0	80.9	32.5	145 100 *b
8.0	79.0	32.3	127 400 *
9.0	77.1	32.0	113 500 *
10.0	75.1	31.7	100 100
11.0	73.2	31.4	84 900
12.0	71.2	31.1	73 800
13.0	69.2	30.7	65 100
14.0	67.1	30.3	58 000
15.0	65.1	29.8	52 300
16.0	62.9	29.3	47 500
18.0	58.6	28.1	39 800
20.0	54.0	26.7	34 000
22.0	49.1	25.0	29 500
24.0	43.8	23.1	25 900
26.0	37.9	20.6	22 900
28.0	31.0	17.6	20 400
30.0	22.2	13.4	18 200
33.5m (110 Ft.) BOOM			
6.7	82.3	35.6	151 000 *
7.0	81.8	35.5	145 100 *
8.0	80.0	35.4	127 200 *
9.0	78.3	35.2	113 200 *
10.0	76.5	34.9	100 200
11.0	74.8	34.6	84 900
12.0	73.0	34.3	73 800
13.0	71.2	34.0	65 000
14.0	69.3	33.6	58 000
15.0	67.5	33.2	52 200
16.0	65.6	32.7	47 300
18.0	61.7	31.7	39 700
20.0	57.7	30.4	33 900
22.0	53.5	29.0	29 400
24.0	49.1	27.3	25 800
26.0	44.3	25.4	22 800
28.0	39.0	23.0	20 300
30.0	33.1	20.2	18 200
32.0	25.8	16.5	16 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
36.6m (120 Ft.) BOOM			
6.7	82.9	38.7	147 100 *
7.0	82.5	38.6	143 000 *
8.0	80.9	38.5	127 000 *
9.0	79.3	38.3	113 100 *
10.0	77.7	38.0	100 300
11.0	76.1	37.8	85 000
12.0	74.4	37.5	73 800
13.0	72.8	37.2	65 000
14.0	71.1	36.8	58 000
15.0	69.5	36.5	52 200
16.0	67.8	36.1	47 300
18.0	64.3	35.1	39 700
20.0	60.7	34.0	33 900
22.0	57.0	32.8	29 400
24.0	53.2	31.3	25 700
26.0	49.1	29.6	22 800
28.0	44.7	27.7	20 200
30.0	40.0	25.4	18 100
32.0	34.7	22.7	16 300
34.0	28.5	19.3	14 700
36.0	20.6	14.7	13 300
39.6m (130 Ft.) BOOM			
7.3	82.6	41.7	133 800 *
8.0	81.6	41.6	127 200 *
9.0	80.1	41.4	112 900 *
10.0	78.6	41.2	100 400
11.0	77.2	40.9	85 000
12.0	75.7	40.7	73 800
13.0	74.2	40.4	65 100
14.0	72.6	40.1	58 000
15.0	71.1	39.7	52 200
16.0	69.6	39.4	47 300
18.0	66.4	38.5	39 700
20.0	63.2	37.5	33 900
22.0	59.9	36.4	29 400
24.0	56.4	35.1	25 700
26.0	52.8	33.6	22 700
28.0	49.1	31.9	20 200
30.0	45.1	30.0	18 100
32.0	40.7	27.8	16 300
34.0	36.0	25.2	14 700
36.0	30.5	22.0	13 300
38.0	24.0	18.0	12 000



Liftcrane Boom Capacities

Meets
ANSI B30.5
Requirements


Boom No. 82 or 22EL
67 860 kg Counterweight
Rating Over End of Blocked Crawlers
No Travel - Limited Swing

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
42.7m (140 Ft.) BOOM			
7.9	82.3	44.7	128 000 *
8.0	82.2	44.6	126 800 *
9.0	80.8	44.5	112 800 *
10.0	79.5	44.3	100 300
11.0	78.1	44.1	85 000
12.0	76.7	43.8	73 800
13.0	75.3	43.6	65 000
14.0	73.9	43.3	58 000
15.0	72.5	43.0	52 200
16.0	71.1	42.6	47 300
18.0	68.2	41.8	39 600
20.0	65.3	40.9	33 800
22.0	62.2	39.9	29 300
24.0	59.1	38.7	25 600
26.0	55.9	37.4	22 600
28.0	52.6	35.9	20 100
30.0	49.1	34.2	18 000
32.0	45.4	32.3	16 200
34.0	41.4	30.1	14 600
36.0	37.0	27.6	13 200
38.0	32.2	24.6	11 900
40.0	26.6	20.9	10 800
42.0	19.4	16.0	9 800
45.7m (150 Ft.) BOOM			
7.9	82.8	47.7	120 400 *
8.0	82.7	47.7	120 100 *
9.0	81.4	47.6	113 100 *
10.0	80.2	47.4	100 100
11.0	78.9	47.2	85 000
12.0	77.6	47.0	73 800
13.0	76.3	46.7	65 000
14.0	75.0	46.4	57 900
15.0	73.7	46.2	52 100
16.0	72.4	45.8	47 100
18.0	69.7	45.1	39 500
20.0	67.0	44.3	33 700
22.0	64.3	43.3	29 100
24.0	61.4	42.3	25 500
26.0	58.5	41.1	22 500
28.0	55.5	39.7	20 000
30.0	52.3	38.2	17 800
32.0	49.1	36.5	16 000
34.0	45.6	34.6	14 400
36.0	41.9	32.5	13 000
38.0	37.9	30.0	11 800
40.0	33.6	27.2	10 700
42.0	28.6	23.7	9 700
44.0	22.6	19.4	8 700

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
48.8m (160 Ft.) BOOM			
8.5	82.5	50.7	107 000 *
9.0	82.0	50.7	107 000 *
10.0	80.8	50.5	100 400
11.0	79.6	50.3	84 900
12.0	78.4	50.1	73 700
13.0	77.2	49.9	64 900
14.0	76.0	49.6	57 800
15.0	74.8	49.3	52 000
16.0	73.5	49.0	47 000
18.0	71.1	48.4	39 400
20.0	68.5	47.6	33 600
22.0	66.0	46.7	29 000
24.0	63.4	45.7	25 300
26.0	60.7	44.6	22 400
28.0	57.9	43.4	19 800
30.0	55.1	42.1	17 700
32.0	52.1	40.5	15 900
34.0	49.1	38.8	14 300
36.0	45.8	37.0	12 900
38.0	42.4	34.8	11 700
40.0	38.7	32.4	10 500
42.0	34.7	29.7	9 600
44.0	30.2	26.4	8 700
46.0	25.0	22.5	7 800
48.0	18.5	17.3	7 100
51.8m (170 Ft.) BOOM			
8.5	83.0	53.8	105 500 *
9.0	82.5	53.7	104 000 *
10.0	81.3	53.6	99 200
11.0	80.2	53.4	84 900
12.0	79.1	53.2	73 600
13.0	78.0	53.0	64 900
14.0	76.8	52.8	57 700
15.0	75.7	52.5	51 900
16.0	74.5	52.2	47 000
18.0	72.2	51.6	39 300
20.0	69.9	50.9	33 500
22.0	67.5	50.1	28 900
24.0	65.1	49.2	25 200
26.0	62.6	48.1	22 200
28.0	60.0	47.0	19 700
30.0	57.4	45.8	17 600
32.0	54.7	44.4	15 800
34.0	52.0	42.8	14 200
36.0	49.1	41.1	12 800
38.0	46.0	39.3	11 600
40.0	42.8	37.2	10 500
42.0	39.4	34.8	9 500
44.0	35.7	32.1	8 600
46.0	31.6	29.1	7 700
48.0	27.0	25.4	7 000
50.0	21.5	20.8	6 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
54.9m (180 Ft.) BOOM			
9.1	82.7	56.8	93 600 *
10.0	81.8	56.7	93 600 *
11.0	80.8	56.5	84 900
12.0	79.7	56.3	73 600
13.0	78.6	56.1	64 800
14.0	77.6	55.9	57 600
15.0	76.5	55.6	51 800
16.0	75.4	55.4	46 900
18.0	73.2	54.8	39 200
20.0	71.0	54.1	33 300
22.0	68.8	53.4	28 800
24.0	66.5	52.5	25 100
26.0	64.2	51.6	22 100
28.0	61.9	50.5	19 600
30.0	59.5	49.4	17 500
32.0	57.0	48.1	15 600
34.0	54.4	46.7	14 100
36.0	51.8	45.1	12 600
38.0	49.0	43.4	11 400
40.0	46.2	41.6	10 300
42.0	43.2	39.5	9 300
44.0	40.0	37.2	8 400
46.0	36.6	34.6	7 600
48.0	32.8	31.6	6 900
50.0	28.6	28.2	6 200
52.0	23.8	24.0	5 600



Liftcrane Boom Capacities

Meets
ANSI B30.5
Requirements


Boom No. 82 or 22EL
67 860 kg Counterweight
Rating Over End of Blocked Crawlers
No Travel - Limited Swing

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
57.9m (190 Ft.) BOOM			
9.8	82.5	59.8	89 200 *
10.0	82.3	59.8	88 600 *
11.0	81.3	59.6	85 000
12.0	80.3	59.4	73 500
13.0	79.2	59.2	64 700
14.0	78.2	59.0	57 600
15.0	77.2	58.8	51 700
16.0	76.2	58.5	46 700
18.0	74.2	58.0	39 000
20.0	72.1	57.3	33 200
22.0	70.0	56.6	28 600
24.0	67.8	55.8	24 900
26.0	65.7	54.9	22 000
28.0	63.5	54.0	19 400
30.0	61.2	52.9	17 300
32.0	58.9	51.7	15 500
34.0	56.6	50.4	13 800
36.0	54.1	49.0	12 400
38.0	51.6	47.4	11 200
40.0	49.0	45.7	10 100
42.0	46.3	43.9	9 100
44.0	43.5	41.8	8 200
46.0	40.5	39.6	7 400
48.0	37.3	37.0	6 700
50.0	33.9	34.2	6 000
52.0	30.0	30.9	5 400
54.0	25.7	27.0	4 800
56.0	20.5	22.1	4 200
61.0m (200 Ft.) BOOM			
9.8	82.9	62.9	80 200 *
10.0	82.7	62.8	80 200 *
11.0	81.7	62.7	80 100
12.0	80.7	62.5	74 000
13.0	79.8	62.3	64 600
14.0	78.8	62.1	57 500
15.0	77.9	61.9	51 600
16.0	76.9	61.7	46 700
18.0	75.0	61.2	38 900
20.0	73.0	60.6	33 000
22.0	71.0	59.9	28 500
24.0	69.0	59.1	24 800
26.0	67.0	58.3	21 800
28.0	64.9	57.4	19 200
30.0	62.8	56.4	17 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
61.0m (200 Ft.) BOOM			
32.0	60.7	55.3	15 300
34.0	58.5	54.1	13 700
36.0	56.2	52.7	12 300
38.0	53.9	51.3	11 000
40.0	51.5	49.7	10 000
42.0	49.0	48.0	9 000
44.0	46.5	46.2	8 100
46.0	43.8	44.2	7 200
48.0	41.0	41.9	6 500
50.0	38.0	39.4	5 800
52.0	34.8	36.6	5 200
54.0	31.2	33.5	4 600
56.0	27.3	29.8	4 100
58.0	22.8	25.4	3 600
64.0m (210 Ft.) BOOM			
10.4	82.7	65.9	77 700 *
11.0	82.1	65.8	76 700 *
12.0	81.2	65.6	73 200
13.0	80.3	65.4	64 500
14.0	79.4	65.2	57 400
15.0	78.5	65.0	51 500
16.0	77.5	64.8	46 500
18.0	75.7	64.3	38 800
20.0	73.8	63.7	32 900
22.0	72.0	63.1	28 300
24.0	70.1	62.4	24 700
26.0	68.1	61.6	21 600
28.0	66.2	60.7	19 100
30.0	64.2	59.8	17 000
32.0	62.2	58.8	15 100
34.0	60.1	57.6	13 600
36.0	58.0	56.4	12 100
38.0	55.9	55.1	10 900
40.0	53.7	53.6	9 800
42.0	51.4	52.0	8 800
44.0	49.0	50.3	7 900
46.0	46.6	48.5	7 100
48.0	44.1	46.5	6 400
50.0	41.4	44.3	5 700
52.0	38.6	41.8	5 100
54.0	35.6	39.1	4 500
56.0	32.3	36.1	4 000
58.0	28.7	32.6	3 500
60.0	24.6	28.5	3 000
62.0	19.7	23.4	2 500

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
67.1m (220 Ft.) BOOM			
10.4	83.0	68.9	70 300 *
11.0	82.5	68.8	70 100 *
12.0	81.6	68.7	69 800 *
13.0	80.7	68.5	64 600
14.0	79.9	68.3	57 200
15.0	79.0	68.2	51 400
16.0	78.1	67.9	46 400
18.0	76.4	67.5	38 600
20.0	74.6	66.9	32 700
22.0	72.8	66.3	28 200
24.0	71.0	65.6	24 500
26.0	69.2	64.9	21 500
28.0	67.3	64.1	19 000
30.0	65.5	63.2	16 800
32.0	63.6	62.2	15 000
34.0	61.6	61.1	13 400
36.0	59.6	60.0	12 000
38.0	57.6	58.7	10 700
40.0	55.6	57.4	9 600
42.0	53.5	55.9	8 600
44.0	51.3	54.4	7 700
46.0	49.0	52.6	6 900
48.0	46.7	50.8	6 200
50.0	44.3	48.8	5 500
52.0	41.8	46.6	4 900
54.0	39.1	44.2	4 300
56.0	36.3	41.6	3 800
58.0	33.2	38.6	3 300
60.0	29.9	35.3	2 800
62.0	26.2	31.4	2 400
64.0	21.9	26.8	2 000



Liftcrane Boom Capacities

Meets
ANSI B30.5
 Requirements

Boom No. 82 or 22EL
67 860 kg Counterweight
Rating Over End of Blocked Crawlers
No Travel - Limited Swing

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
70.1m (230 Ft.) BOOM			
11.0	82.8	71.9	63 100 *
12.0	82.0	71.8	62 800 *
13.0	81.1	71.6	62 200
14.0	80.3	71.4	57 200
15.0	79.5	71.3	51 200
16.0	78.6	71.1	46 300
18.0	77.0	70.6	38 500
20.0	75.3	70.1	32 600
22.0	73.6	69.5	28 000
24.0	71.9	68.9	24 300
26.0	70.1	68.2	21 300
28.0	68.4	67.4	18 700
30.0	66.6	66.5	16 600
32.0	64.8	65.6	14 700
34.0	63.0	64.6	13 200
36.0	61.1	63.5	11 700
38.0	59.2	62.3	10 500
40.0	57.3	61.1	9 400
42.0	55.3	59.7	8 400
44.0	53.3	58.2	7 500
46.0	51.2	56.7	6 700
48.0	49.0	54.9	6 000
50.0	46.8	53.1	5 300
52.0	44.5	51.1	4 700
54.0	42.1	48.9	4 100
56.0	39.6	46.6	3 600
58.0	36.9	44.0	3 100
60.0	34.0	41.1	2 600
62.0	30.9	37.9	2 200
64.0	27.5	34.3	1 800

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
73.2m (240 Ft.) BOOM			
11.6	82.6	74.9	57 200 *
12.0	82.3	74.9	57 100 *
13.0	81.5	74.7	56 800 *
14.0	80.7	74.5	56 500 *
15.0	79.9	74.4	51 100
16.0	79.1	74.2	46 100
18.0	77.5	73.7	38 300
20.0	75.9	73.2	32 400
22.0	74.3	72.7	27 800
24.0	72.6	72.1	24 100
26.0	71.0	71.4	21 100
28.0	69.3	70.7	18 600
30.0	67.6	69.8	16 400
32.0	65.9	69.0	14 600
34.0	64.2	68.0	13 000
36.0	62.4	67.0	11 600
38.0	60.6	65.9	10 300
40.0	58.8	64.7	9 200
42.0	56.9	63.4	8 200
44.0	55.0	62.0	7 300
46.0	53.1	60.5	6 500
48.0	51.1	59.0	5 800
50.0	49.0	57.2	5 100
52.0	46.9	55.4	4 500
54.0	44.7	53.4	3 900
56.0	42.4	51.3	3 400
58.0	40.0	49.0	2 900
60.0	37.5	46.4	2 400
62.0	34.8	43.6	2 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
76.2m (250 Ft.) BOOM			
11.6	82.9	78.0	51 900 *
12.0	82.6	77.9	51 800 *
13.0	81.9	77.8	51 500 *
14.0	81.1	77.6	51 200 *
15.0	80.3	77.5	50 500
16.0	79.6	77.3	47 400
18.0	78.0	76.9	38 500
20.0	76.5	76.4	32 600
22.0	74.9	75.9	28 000
24.0	73.4	75.3	24 300
26.0	71.8	74.6	21 300
28.0	70.2	73.9	18 700
30.0	68.6	73.1	16 600
32.0	66.9	72.3	14 700
34.0	65.3	71.4	13 200
36.0	63.6	70.4	11 700
38.0	61.9	69.4	10 500
40.0	60.2	68.2	9 400
42.0	58.4	67.0	8 400
44.0	56.6	65.7	7 500
46.0	54.8	64.3	6 700
48.0	52.9	62.8	5 900
50.0	51.0	61.3	5 300
52.0	49.0	59.5	4 700
54.0	47.0	57.7	4 100
56.0	44.9	55.7	3 500
58.0	42.7	53.6	3 100
60.0	40.4	51.3	2 600
62.0	38.0	48.8	2 200
64.0	35.4	46.1	1 800